Data Sheet



Coaxial Panel Connector 22_MMCX-50-0-4/111_O

Description

Straight bulkhead receptacle jack

Interface standards
SUHNER-MMCX



Technical Data

Electrical Data

 $\begin{array}{ll} \text{Impedance} & 50 \, \Omega \\ \text{Interface frequency max.} & 6 \, \text{GHz} \end{array}$

Mechanical Data

 Chassis torque
 0.4 Nm

 Number of matings
 500

 Weight
 0.0003 kg

Environmental Data

Operating temperature -55 °C to 155 °C 2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	

Related Documents

Outline drawing DOU-00010462
Catalogue drawing DCA-00010464
Mounting hole DOU-00009144

Ordering Information

Bulk 100 pcs package 22_MMCX-50-0-4/111_OH

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.