



TRSF AND XLRM WIRING CHART							
JACKET COLOR	H.S. TUBING MARKING	END "A" TRS FEMALE			END "B" XLR MALE		
		RED	BLACK	BARE	RED	BLACK	BARE
BROWN	CHANNEL 1	TIP	RING	SLEEVE	PIN "2"	PIN "3"	PIN "1"
RED	CHANNEL 2	TIP	RING	SLEEVE	PIN "2"	PIN "3"	PIN "1"
ORANGE	CHANNEL 3	TIP	RING	SLEEVE	PIN "2"	PIN "3"	PIN "1"
YELLOW	CHANNEL 4	TIP	RING	SLEEVE	PIN "2"	PIN "3"	PIN "1"
GREEN	CHANNEL 5	TIP	RING	SLEEVE	PIN "2"	PIN "3"	PIN "1"
BLUE	CHANNEL 6	TIP	RING	SLEEVE	PIN "2"	PIN "3"	PIN "1"
PURPLE	CHANNEL 7	TIP	RING	SLEEVE	PIN "2"	PIN "3"	PIN "1"
GRAY	CHANNEL 8	TIP	RING	SLEEVE	PIN "2"	PIN "3"	PIN "1"

PART NUMBER	CABLE LENGTH "X"
TRSF05XLRM	5.00 FT +/- 1.50 IN
TRSF10XLRM	10.00 FT +/- 1.50 IN

NOTES:

- CABLE BREAKOUT LENGTH IS 18.00 +/- 0.75 IN.
- CABLE IS SHIPPED COILED AND PACKAGED IN A BAG.
- MATERIALS:

TRS FEMALE:

HOUSING AND HANDLE - COPPER ALLOY, NICKEL PLATED  
 SPRINGS AND GROUND CLIP - COPPER ALLOY  
 CABLE CLAMP - STEEL, TIN PLATED  
 INSULATION - NYLON  
 WASHER - PHENOLIC

CABLE - COPPER, THERMOPLASTIC

XLR MALE CONNECTOR:

HANDLE - ZINC ALLOY, NICKEL PLATED  
 HOUSING - ZINC ALLOY  
 INSULATOR - THERMOPLASTIC  
 GROUND TERMINAL - SPECIAL COPPER ALLOY  
 CONTACT PINS - COPPER ALLOY, SILVER FINISH

**CUSTOMER DRAWING**

REV	ECO NUMBER	DATE	BY	APVD
B	26637	10/11/10	RS	TJK
A	25983	10/30/08	RS	TJK

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES  
 - TWO PLACE DECIMALS ±0.02  
 - THREE PLACE DECIMALS ±0.005

DO NOT SCALE DRAWING

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.							
SIZE	WIDTH	MULT	LBS/M	TEMPER			
FINISH SPEC No.				MATERIAL SPEC No.			
FIRST USED ON			SCALE 1:2				
DATE DRAWN	BY	CHKD	APVD				
4/14/08	JGK	RS	TJK				
			1/3/11				
NAME				PART No.		REV	
TRSF FEMALE TO XLR MALE, RoHS				TRSF__XLRM		B	