

## RF TERMINATION Type 6525.41.AB

### Description

Standard Termination, Medium Power



### Product Configuration

Connector 7/16 plug (male)  
Interface standards IEC 60169-4\_CECC 22190\_DIN 47223\_VG 95250

### Technical Data

#### Electrical Data

Nominal Impedance 50  $\Omega$   
Frequency range 0 to 2 GHz  
VSWR max. 1.1  
Power rating 25 Watt average power up to 25 °C ambient temperature, linearly derated to 0 Watt at 150 °C ambient temperature.  
1500 Watt peak power , 5  $\mu$ s pulse, 0.05 % duty cycle

#### Mechanical Data

Weight 0.204 kg

#### Environmental Data

Operating temperature -40 °C to 150 °C  
2011/65/EU (RoHS - including 2015/863 and 2017/2102) compliant

#### Material Data

Piece Part	Material	Surface Plating
Centre contact	Brass	Silver Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Aluminium	Anodized
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

### Related Documents

Outline drawing DOU-00005462

### Ordering Information

Single Packaging 6525.41.AB  
Packaging

### Additional Information

Important note WARNING Beryllia Ceramic Inside! DO NOT sand, scrap or tamper with. Dispose in accordance with all relevant regulations.