

## LR2-RS

~9.6° spot beam optimized for LUXEON Rebel ES. 14.8 mm high assembly with installation tape.

### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.6 mm
Height	14.8 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ


### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LXP2-RS	Single lens	PMMA	clear	
LR2-ES-LH1-HLD	Holder	PC	white	
HEIDI-TAPE	Tape	PU tape	black	

### ORDERING INFORMATION:

Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
CA11929_LR2-RS	Single lens	1680	336	112	9.3
» Box size: 480 x 280 x 300 mm					





This drawing is our property. It can't be reproduced or communicated without our written agreement.



L  
T  
F  
F

e  
e  
i  
n

d

DRAWING TITLE

Datasheet LR2-ES series assy

DRAWN BY: a  
DATE: 21.11.2011

CHECKED BY: s n  
DATE: 21.11.2011

DESIGNED BY: pl  
DATE: 27.08.2010

SIZE: A4  
DRAWING NUMBER: -  
REV: 2


SCALE: 1:1  
WEIGHT (g):  
SHEET: 1/1

See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

### PHOTOMETRIC DATA (MEASURED):




LED XP-L HD  
 FWHM / FWTM 16.0° / 31.0°  
 Efficiency 91 %  
 Peak intensity 8.9 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




LED LUXEON Rebel ES  
 FWHM / FWTM 11.0°  
 Efficiency 94 %  
 LEDs/each optic 1  
 Light colour White  
 Required components:









LED LUXEON T  
 FWHM / FWTM 12.0° / 23.0°  
 Efficiency 91 %  
 Peak intensity 12.2 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED LUXEON TX  
 FWHM / FWTM 11.0° / 23.0°  
 Efficiency 91 %  
 Peak intensity 15.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### PHOTOMETRIC DATA (MEASURED):

<p><b>LUMILEDS</b></p> <p>LED LUXEON Z ES</p> <p>FWHM / FWTM 6.0° / 16.0°</p> <p>Efficiency 91 %</p> <p>Peak intensity 38.3 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>NICHIA</b></p> <p>LED NVSxx19B/NVSxx19C</p> <p>FWHM / FWTM 11.0° / 23.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 16 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSLON Square EC</p> <p>FWHM / FWTM 10.0° / 22.0°</p> <p>Efficiency 92 %</p> <p>Peak intensity 17.6 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED PLPVEC2 850A</p> <p>FWHM / FWTM 5.0° / 12.0°</p> <p>Efficiency %</p> <p>LEDs/each optic 1</p> <p>Light colour IR</p> <p>Required components:</p>		

### PHOTOMETRIC DATA (SIMULATED):


#### CREE

LED XD16  
 FWHM / FWTM 8.0° / 18.0°  
 Efficiency 91 %  
 Peak intensity 22.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### CREE

LED XP-G2  
 FWHM / FWTM 10.0° / 20.0°  
 Efficiency 95 %  
 Peak intensity 22.2 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### CREE

LED XQ-E HD  
 FWHM / FWTM 7.0° / 15.0°  
 Efficiency 92 %  
 Peak intensity 39 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### CREE


LED XQ-E HI  
 FWHM / FWTM 6.0° / 14.0°  
 Efficiency 93 %  
 Peak intensity 47.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### PHOTOMETRIC DATA (SIMULATED):


#### LUMILEDS

LED LUXEON H50-2  
 FWHM / FWTM 10.5° / 22.0°  
 Efficiency 93 %  
 Peak intensity 17.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### LUMILEDS

LED LUXEON HL2X  
 FWHM / FWTM 12.0° / 24.0°  
 Efficiency 94 %  
 Peak intensity 15.9 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### LUMILEDS

LED LUXEON IR Domed 60  
 FWHM / FWTM 8.0° / 20.0°  
 Efficiency 92 %  
 LEDs/each optic 1  
 Light colour IR  
 Required components:



#### LUMILEDS


LED LUXEON V2  
 FWHM / FWTM 11.0° / 24.0°  
 Efficiency 94 %  
 Peak intensity 16.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### PHOTOMETRIC DATA (SIMULATED):


#### OSRAM Opto Semiconductors

LED OSCONIQ C 2424  
 FWHM / FWTM 8.0° / 20.0°  
 Efficiency 95 %  
 Peak intensity 24 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### OSRAM Opto Semiconductors

LED OSCONIQ P 3030  
 FWHM / FWTM 8.0° / 18.0°  
 Efficiency 94 %  
 Peak intensity 27.8 cd/lm  
 LEDs/each optic 1  
 Light colour Blue  
 Required components:




#### OSRAM Opto Semiconductors

LED OSLON Square CSSRM2/CSSRM3  
 FWHM / FWTM 10.0° / 20.0°  
 Efficiency 95 %  
 Peak intensity 22.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### OSRAM Opto Semiconductors


LED OSLON SSL 120  
 FWHM / FWTM 8.0° / 16.0°  
 Efficiency 95 %  
 Peak intensity 33 cd/lm  
 LEDs/each optic 1  
 Light colour Amber  
 Required components:



### PHOTOMETRIC DATA (SIMULATED):


#### OSRAM Opto Semiconductors

LED SFH 4715AS  
FWHM / FWTM 8.0° / 20.0°  
Efficiency 94 %  
Peak intensity 23.4 cd/lm  
LEDs/each optic 1  
Light colour IR  
Required components:



#### OSRAM Opto Semiconductors

LED SFH 4770S  
FWHM / FWTM 8.0° / 18.0°  
Efficiency 95 %  
Peak intensity 29.9 cd/lm  
LEDs/each optic 1  
Light colour IR  
Required components:





### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)