

Specification Sheet

Part Number: T18L3M4



Cable Tie, 8" Long, UL Rated, 18lb Tensile Strength, PA66, Orange, 1000/pkg

| | |
|--------------------------------|---|
| Article Number | 111-02030 |
| Type | T18L |
| Color | Orange (OG) |
| Features & Benefits | <ul style="list-style-type: none">• Inside serrations allow for strong grip on cables and wire bundles.• Head design provides high tensile strength with very low insertion force.• Bent tail ensures a quick and simple installation. |
| Quantity Per | bag |
| Product Description | HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Short Description | Cable Tie, 8" Long, UL Rated, 18lb Tensile Strength, PA66, Orange, 1000/pkg |

Global Part Name

T18L-PA66-OG

Minimum Tensile Strength (Imperial)

18.0

Minimum Tensile Strength (Metric)

80.0

Length L (Imperial)

8.0

Length L (Metric)

203.2

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.10

Width W (Metric)

2.5

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.5

Bundle Diameter Max (Imperial)

2.17

Bundle Diameter Max (Metric)

55.0

Thickness T (Metric)

1.1

| | |
|-----------------|----------------------|
| Material | Polyamide 6.6 (PA66) |
|-----------------|----------------------|

| | |
|--------------------------|------|
| Material Shortcut | PA66 |
|--------------------------|------|

| | | |
|--------------------|------------|---------------------|
| US MIL SPEC | MS3367-4-3 | Flammability |
|--------------------|------------|---------------------|

| | |
|----------|---------------------|
| UL 94 V2 | Halogen free |
|----------|---------------------|

| | |
|-----|---------------------------------------|
| Yes | Operating Temperature (Metric) |
|-----|---------------------------------------|

| | |
|----------------------------------|-----------------------|
| -40°F to +185°F (-40°C to +85°C) | ROHS Complaint |
|----------------------------------|-----------------------|

| | |
|-----|--|
| Yes | Certification/Specification WEB |
|-----|--|

| | |
|-----------------|---------------------------|
| UL-ZODZ2.E64139 | UL Recognized (US) |
|-----------------|---------------------------|

| | |
|-----|----------------------------------|
| Yes | UL Listed (US and Canada) |
|-----|----------------------------------|

| | |
|-----|--------------------------------------|
| Yes | UL Recognized (US and Canada) |
|-----|--------------------------------------|

| | |
|-----|-----------------------|
| Yes | UL Listed (US) |
|-----|-----------------------|

Yes

| | |
|-----------------------------------|------|
| Package Quantity(Imperial) | 1000 |
|-----------------------------------|------|

| | |
|----------------------------------|------|
| Package Quantity (Metric) | 1000 |
|----------------------------------|------|

| | |
|-----------------------|------------|
| Customs Number | 3926909988 |
|-----------------------|------------|

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)