


TECHNICAL DATA SHEET

Part#: 500-210A-US

Pliers - Multiple Lead Forming - 1st bend .10" from body - Adjustable
Designed to form transistor leads with .100" center spacing

The 500-210A-US 4.75" adjustable multiple lead forming plier is designed to form transistor leads with .100" center spacing. Leads are formed at 90° for through-hole mounting. The distance from the component body to the bend is adjustable from .100" (2.5mm) to .300" (7.5mm). It features an ergonomically molded antimicrobial Anti-Static grip (10^{10} ohms/sq surface resistivity) with dual leaf springs.

• Precision Level	★★★★★
• Material	Carbon
• Surface Resistivity	10^{10} ohms/sq
• Shape	Straight
• Type of Cut	n/a
• Cutting Capacity	n/a
• Blade Angle	
• Blade Length	.900"
• Body Width	0.42" (10.5mm)
• Body Height	
• OAL	4.75" (118.75mm)
• Weight (OZ)	5
• UPC	662847006920
• Schedule B	8203.20.60.30
• ECCN	EAR99
• UNSPSC Code	
• Country of Origin	USA
• Group	500 Series



EXCELTA
CORPORATION

500-210A-US
COMPONENT FORMING

A = .100"
B = .265"

(Drawing not to scale)