



NOTES:

1. PLUG FINGER SAME AS 290 PLUG.
2. PLUG FINGER, INSULATOR, HANDLE AND FLEX RELIEF SHIPPED UNASSEMBLED.
3. ASSEMBLE FLEX RELIEF TO HANDLE BEFORE INSERTING CABLE.
4. MATERIALS:
 PLUG ASSEMBLY - COPPER ALLOY, NICKEL PLATED
 TERMINALS - COPPER ALLOY, TIN PLATED
 INSULATORS - MYLAR, PHENOLIC AND THERMOPLASTIC
 SCREWS - STEEL, NICKEL PLATED
 HANDLE - ZINC ALLOY, NICKEL PLATED
 FLEX RELIEF - THERMOPLASTIC RUBBER, BLACK
5. THIS PRODUCT IS RoHS COMPLIANT.

CABLE SIZE
SEE TABLE

PARTNUMBER	RECOMMENDED FLEX RELIEF CABLE RANGE
290F	Ø0.220 - Ø0.190 [Ø5.59 - Ø4.83]
290FL	Ø0.250 - Ø0.220 [Ø6.35 - Ø5.59]

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.				
					SIZE	WIDTH	MULT	LBS/M	TEMPER
					FINISH			MATERIAL	
					SPEC No.			SPEC No.	
					FIRST USED ON		SCALE 5:4		
					DATE DRAWN	BY	CHKD	APVD	
					6/19/17	AB	AB	TJK	
							6/19/17	2/16/22	
					NAME 290 PLUG WITH SLEEK HANDLE AND FLEX RELIEF, RoHS			PART No. 290F - 290FL	
					DO NOT SCALE DRAWING			REV A	
A	28475	02/21/22	PC	TJK					
REV	ECO NUMBER	DATE	BY	APVD					
REVISIONS									