



NOTES
 1 LOCKWASHER: C51000 PHOSPHOR BRONZE / 96-00034
 2 - EFFECTIVE THREAD LENGTH TO BE WITHIN .024 OF LOCKWASHER

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE: <input checked="" type="checkbox"/> US Incht <input type="checkbox"/> SI mm <input type="checkbox"/> DM CUSTOMARY METRIC		DIMENSIONS ARE TO BE MET BEFORE PROTECTIVE COATINGS ARE APPLIED	THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL'S MICRO SWITCH DIVISION. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF HONEYWELL.	C B A	SPK OCT04 KSR JUL04 CCK NOV 98
		TITLE SCREW, ASSEMBLED WASHER, BINDING HEAD, COMBINATION		REVISION	REVISION NOTICE
		MATERIAL C26000 COPPER ZINC (BRASS) / 96-00020 (50)		REPLACES	CHECKED BY
CAD DRAWN 11 NOV 98 RASTER DESIGN CHECK 11 NOV 98	Honeywell MICRO SWITCH	THIRD ANGLE PROJECTION DO NOT SCALE PRINT	SCALE 5:1 ISSUE 10	DRAWING NUMBER 10-21737	