

ICM48 / ICM60 Series

48W / 65W International Adapters

- DOE Level VI Efficiency Rating
- Universal Input: 90 ~ 264Vac, 47/63 Hz
- UL/cUL Safety Approved
- Corded DC Output Connector
- US, UK, AU & EU AC adapters available
- Light Weight and Compact



Model No.	Application	Output Connector	Output Voltage	Output Current			Voltage Accuracy	Ripple Noise	Line Reg.	Load Reg.
				Min	Rated	Peak				
ICM48-090	ITE	2.1mm I.D. x 5.5mm O.D. x 9.5mm Barrel	+9.0V	0	5.3	—	±5%	< ± 1%	± 1%	± 5%
ICM48-120	ITE		+12.0V	0	4.0	—	±5%	< ± 1%	± 1%	± 5%
ICM48-180	ITE		+18.0V	0	2.7	—	±5%	< ± 1%	± 1%	± 5%
ICM48-240	ITE		+24.0V	0	2.0	—	±5%	< ± 1%	± 1%	± 5%
ICM48-360	ITE		+36.0V	0	1.3	—	±5%	< ± 1%	± 1%	± 5%
ICM48-480	ITE		+48.0V	0	1.0	—	±5%	< ± 1%	± 1%	± 5%
ICM60-090	ITE		+9.0V	0	6.0	—	±5%	< ± 1%	± 1%	± 5%
ICM60-120	ITE		+12.0V	0	5.0	—	±5%	< ± 1%	± 1%	± 5%
ICM60-180	ITE		+18.0V	0	3.3	—	±5%	< ± 1%	± 1%	± 5%
ICM60-240	ITE		+24.0V	0	2.5	—	±5%	< ± 1%	± 1%	± 5%
L6R60-360	ITE		+36.0V	0	1.8	—	±5%	< ± 1%	± 1%	± 5%
L6R60-480	ITE		+48.0V	0	1.3	—	±5%	< ± 1%	± 1%	± 5%

- Output voltages from 5.0Vdc to 48.0Vdc are available in increments of 0.1V. Please contact Tri-Mag, LLC for the part number and specifications for your output voltage requirement and application. Output voltages from 6.0V to 8.9V do not meet Level VI efficiency requirements and are subject to associated importation regulations.
- The output voltage is verified to specs at 60 percent rated load condition.
- The **line regulation** is defined by changing ± 10 percent of input voltage from the nominal line at rated load.
- The **load regulation** is defined by changing ± 40 percent of the measured output load from 60 percent of the rated load.
- The **ripple and noise** is measured by using 20MHz bandwidth limited oscilloscope with each output terminated with a 10 µF electrolytic and a 0.1 µF capacitor at rated load and nominal line.
- The **efficiency** is measured at rated load and nominal line.

ICM48 / ICM60 Series

Economical and dependable international adapter whether powering stationary or portable devices.

This DOE Level VI compliant power supply/adapter is rated up to 65W, with plenty of voltage levels to

choose from: 5.0Vdc to 48.0Vdc (in increments of 0.1V), to match your specific need.

Call us (800-657-0853) for the part number to match your particular need.

Specifications

Input

Input Voltage	• 90 Vac ~ 264 Vac
Input Frequency	• 47 Hz to 63 Hz
No Load Input Power	• < 0.1W
Input Current	• 1.2A Max.
Inrush Current	• 40A Max.
Leakage Current	• 0.25mA Max.
Input Connection	• US (others available)

Output

Output Voltage Range	• 5.0 to 48.0 Vdc
Output Current Range	• L6R48: 5.3 - 1.3 A, 48W Max. • L6R60: 6.0 - 1.6A, 65W Max.
Minimum Load	• No min. load required.
Line Regulation	• $\pm 1\%$ at rated load across input voltage range
Load Regulation	• $\pm 5\%$
Ripple & Noise	• < 1%, 240mVp-p Max.
Overvoltage Protection	• Auto recovery
Overload Protection	• Auto recovery
Short Circuit Protection	• Auto recovery

General

Insulation Resistance	• 50M Ω Min.
Efficiency	• Level VI compliant
MTBF	• 50,000 hrs to MIL-HDBK-217F at +25°C

Environmental

Operating Temperature	• 0°C to 40°C
Operating Humidity	• 5% - 95% RH, Non-Condensing
Storage Temperature	• -20°C to +80°C

EMC & Safety

Safety Approvals	• UL: UL60950-1 • cUL: UL60950-1
EMC Approvals	• FCC

Warranty

Warranty Period	• 3 years
-----------------	-----------

Dimensions and Notes

Dimensions in mm	
Tolerance	• $\pm 0.2\text{mm}$
Size	• 117.3 x 54.5 x 41.2 mm • 4.62 x 2.15 x 1.62 Inches
Weight	• Approx. 200g (7.0oz.)
Connectors	• AC input, US, UK, AU and EU adapters available • DC output, standard 2.1mm x 5.5mm x 9.5mm corded dc barrel connector or per customer specification.
Cord length	• 1000 \pm 20 mm (39.3 \pm .8")

Mechanical Drawing

