



CORE DIMENSIONS				35T0155-00P	
UNCOATED CORE					
	MM	INCHES		MM	INCHES
OD	3.94	(.155)	±	.13	(.005)
ID	2.24	(.088)	±	.13	(.005)
TH	2.54	(.100)	±	.13	(.005)
SINGLE PARAYLENE					
OD	3.96	(.156)	±	.13	(.005)
ID	2.21	(.087)	±	.13	(.005)
TH	2.57	(.101)	±	.13	(.005)

WEIGHT / K 0.1022 KGS .2252 LBS

INITIAL PERMEABILITY 5000

ROOM TEMPERATURE ELECTRICAL SPECIFICATION									
	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	GAUSS	TURNS
L	-20.0%	1.15	1.438	1.73	20.0%	100	0.93	10	1
Q		10				100	0.93	10	1

COATING SPECIFICATIONS			
TYPE	Max. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
Paraylene	(0.0127 / 0.5)	1000	.13

NOTES:

1. Cosmetic Specification refer to WI-QA-015.



Rev	Description	Date	INT
C	Transfer to Lotus Notes	1997/11/19	I.S
D	Delte 35T0155-00Q Spec, Reacitve the print	2007/11/19	Song
E	Revised template	2019/3/10	Jcai

Date: 2019/3/10	DWG # 35T0155-00P-E	Rev:
Drawn By: Jcai	Title # 35T0155-00P	E

Laird This document contains information which is proprietary to laird. No production or publication of this document in whole or in part shall be made without written authorization from Laird.