

AMP Product applied: Type Designation Description: Various Eng Responsibility: Part No.: Various AMP GB Source: Packaging: (if other than AMP) Specification of materials Application Specification: used in application: Cable: Customer Manual: Insulation: Specification of output 409-5862 product: **Instruction Sheet:** 411-3202 AMP Heavy-Head Adapter 525432-1, is designed to allow a variety of heavy heads to be Cycle rate: Approbation & Conference actuated using an AMP 626 Pneumatic Tooling Assembly. The heavy head adapter (Dependent on operator dexterity) assembly, attaches to the tool holder assembly of the pneumatic tool, to provide the necessary straight line motion of the crimping dies. When actuated, a cam extends through CE approved the tool holder into the adapter, contacting an internal spring-loaded die holder mechanism. **Utilities:** The other end of the mechanism is directly connected to the movable die and as the cam pushes against the mechanism, the movable die moves in a straight line and bottoms against Release Status: the stationary die. When the cam of the pneumatic tool retracts, the force is removed from the movable die and the spring loaded mechanism returns to its starting position. Size: The die may also be opened and closed manually by use of the plastic slide switch, which is 50mm x 100mm Rev "O" coupled to the movable die and the spring loaded mechanism via a screw. The slide switch Weight: therefore permits opening and closing of the dies for insertion and removal of the terminals 0.4 kgIssued: 01/06/98 or splices. Class: By: John Swarbrick 1.1.2

NAME OF TOOL

Heavy H/d Adapter, 626 Tooling

Log No.

525432-1