


Data sheet | Item number: 859-302

Relay module; Nominal input voltage: 5 VDC; 1 changeover contact; Red status indicator; Module width: 6 mm; 2,50 mm<sup>2</sup>; gray






[www.wago.com/859-302](http://www.wago.com/859-302)



Similar to picture

Color:



DC load limit curve

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

**Data****Notes**

## Note

To protect the relay coils and contacts, inductive loads must be dampened with an effective protection circuit.

**Technical data****Control Circuit**

Nominal input voltage $U_N$	DC 5 V
Input voltage range	-15 ... +20 %
Nominal input current at $U_N$	31 mA

**Load circuit**

Number of changeover/switchover contacts	1
Contact material (relay)	AgSnO <sub>2</sub>
Limiting continuous current	5 A
Inrush current (resistive) max.	(AC) 20 A / 0.02 s
Switching voltage (max.)	AC 250 V
Switching power (resistive) max.	AC 1250 VA; DC (see load limit curve)
Switching capacity	AC-15: 3 A / AC 250 V; DC-13: 2 A / DC 24 V
Recommended minimum load	10 V / 10 mA; 24 V / 1 mA
Pull-in time (typ.)	15 ms
Drop-out time (typ.)	25 ms
Bounce time (typ.)	3.5 ms
Electrical life (NO; resistive load; 23 °C)	50 x 10 <sup>3</sup> switching operations
Mechanical life	5 x 10 <sup>6</sup> switching operations
Switching frequency with/without load (max.)	6 min <sup>-1</sup> / 180 min <sup>-1</sup>

**Signaling**

Status indicator	Red LED
------------------	---------

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



## Safety and protection

Rated voltage	300 V
Rated surge voltage	4 kV
Overvoltage category	III
Pollution degree	2
Dielectric strength (control/load circuit) (AC, 1 min)	4 kVrms
Dielectric strength (open contact) (AC, 1 min)	1 kVrms
Insulation type (control/load circuit)	Reinforced insulation (safe isolation)
Insulation type (adjacent devices)	Reinforced insulation (safe isolation)
Protection type	IP20; in connected state or when using 859-525 end plate

## Connection data

Connection technology	CAGE CLAMP®
Solid conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 14 AWG
Fine-stranded conductor	0.08 ... 2.5 mm <sup>2</sup> / 28 ... 14 AWG
Fine-stranded conductor; with insulated ferrule	0.08 ... 1.5 mm <sup>2</sup> / 28 ... 16 AWG
Strip length	5 ... 6 mm / 0.2 ... 0.24 inches

## Physical data

Width	6 mm / 0.236 inches
Height	91 mm / 3.583 inches
Depth from upper-edge of DIN-rail	56 mm / 2.205 inches

## Mechanical data

Mounting type	DIN-35 rail
Mounting position	Horizontal (standing/lying); vertical

## Material Data

Color	gray
Fire load	0.338 MJ
Weight	22 g

## Environmental requirements

Ambient temperature (operation at U <sub>N</sub> )	-40 ... +50 °C
--	----------------

Subject to changes. Please also observe the further product documentation!



Ambient temperature (storage)	-40 ... +70 °C
Processing temperature	-25 ... +50 °C
Temperature range of connection cable	$\geq (T_{\text{ambient}} + 20 \text{ K})$
Relative humidity	5 ... 95 % (no condensation permissible)
Operating altitude (max.)	2000 m

## Standards and specifications

Standards/specifications	EN 61010-2-201 EN 61810-1 EN 61373 UL 508 DNV
--------------------------	---

## Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
eCl@ss 10.0	27-37-16-01
eCl@ss 9.0	27-37-16-01
ETIM 8.0	EC001437
ETIM 7.0	EC001437
PU (SPU)	10 pcs
Packaging type	box
Country of origin	DE
GTIN	4055143602587
Customs tariff number	85364900990

## Environmental Product Compliance

CAS-No.	7439-92-1 79-94-7
REACH Candidate List Substance	2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol Lead
RoHS Compliance Status	Compliant, With Exemption
RoHS Exemption	7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	f15d9fcf-904d-4626-a484-4e179b1fd086
SCIP notification number (Belgium)	377c4c78-7560-43ba-86c8-88d5c054bab3
SCIP notification number (Bulgaria)	a8a14eb0-0c6b-4956-bece-f10931f44371
SCIP notification number (Czech Republic)	07a7819c-cc39-49d2-a548-fc2bbe42e4e8

Subject to changes. Please also observe the further product documentation!


WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



SCIP notification number (Denmark)	8bc29f39-0d1e-4da5-bbc9-2aec51edac06
SCIP notification number (Finland)	90489025-2017-4a1f-ade5-7a88c04953c3
SCIP notification number (France)	769eea16-43e0-4448-beea-9c51f941ce7f
SCIP notification number (Germany)	3fa2e416-c321-4095-86ae-7923d551546c
SCIP notification number (Hungary)	1845ecb4-d135-44fe-b776-154220a20378
SCIP notification number (Italy)	82109245-4da4-4710-b375-63ad6339156f
SCIP notification number (Netherlands)	a2fca02b-4159-4768-be53-6ced07aab04d
SCIP notification number (Poland)	b3071fe3-6581-4bdb-926a-c23de52a173d
SCIP notification number (Romania)	6b55650a-78d9-4909-a33b-4d20d7165fb6
SCIP notification number (Sweden)	27a25ef8-5adc-447b-a5c3-dc1560beb6c6

## Approvals / Certificates



### General approvals

Logo	Approval	Additional Approval Text	Certificate name
	CCC CNEX	CNCA-C23-01	2021312304000982 (Ex ec nC IIC T4 Gc)

### Declarations of conformity and manufacturer's declarations

Logo	Approval	Additional Approval Text	Certificate name
	EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
	UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

### Approvals for marine applications



Logo	Approval	Additional Approval Text	Certificate name
	DNV DNV Germany GmbH	DNV-CG-0339,Aug.2021	TAA00001D1
	PRS Polski Rejestr Statków	-	TE/2186 /880590/18

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

## Approvals for hazardous areas

Logo	Approval	Additional Approval Text	Certificate name
	CCC CNEX	CNCA-C23-01	2021312304000982 (Ex ec nC IIC T4 Gc)
	UKEx WAGO GmbH & Co. KG	EN 60079-0	UKCA_WAGO22UKEX007X_ec nC

## Optional accessories

## End plate

Intermediate plate

**Item no.: 859-525**

End and intermediate plate; 1 mm thick; gray

[www.wago.com/859-525](http://www.wago.com/859-525)

## Tool

Operating tool

**Item no.: 210-720**

Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

[www.wago.com/210-720](http://www.wago.com/210-720)

## Ferrule

Ferrule

**Item no.: 216-223**Ferrule; Sleeve for 1 mm<sup>2</sup> / AWG 18; insulated; electro-tin plated; red[www.wago.com/216-223](http://www.wago.com/216-223)**Item no.: 216-222**Ferrule; Sleeve for 0.75 mm<sup>2</sup> / 18 AWG; insulated; electro-tin plated; gray[www.wago.com/216-222](http://www.wago.com/216-222)**Item no.: 216-221**Ferrule; Sleeve for 0.5 mm<sup>2</sup> / 20 AWG; insulated; electro-tin plated; white[www.wago.com/216-221](http://www.wago.com/216-221)**Item no.: 216-224**Ferrule; Sleeve for 1.5 mm<sup>2</sup> / AWG 16; insulated; electro-tin plated; black[www.wago.com/216-224](http://www.wago.com/216-224)**Item no.: 216-321**Ferrule; Sleeve for 0.25 mm<sup>2</sup> / AWG 24; insulated; electro-tin plated; yellow[www.wago.com/216-321](http://www.wago.com/216-321)**Item no.: 216-322**Ferrule; Sleeve for 0.34 mm<sup>2</sup> / 22 AWG; insulated; electro-tin plated; light turquoise[www.wago.com/216-322](http://www.wago.com/216-322)

## Jumpers

Jumper

Subject to changes. Please also observe the further product documentation!

WAGO GmbH &amp; Co. KG

Hansastr. 27














32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.


	<p><b>Item no.: 859-408</b> Jumper; for jumper slot; 8-way; insulated; light gray</p>	<a href="http://www.wago.com/859-408">www.wago.com/859-408</a>
	<p><b>Item no.: 859-404/000-005</b> Jumper; for jumper slot; 4-way; insulated; red</p>	<a href="http://www.wago.com/859-404/000-005">www.wago.com/859-404/000-005</a>
	<p><b>Item no.: 859-404/000-006</b> Jumper; for jumper slot; 4-way; insulated; blue</p>	<a href="http://www.wago.com/859-404/000-006">www.wago.com/859-404/000-006</a>
	<p><b>Item no.: 859-405/000-005</b> Jumper; for jumper slot; 5-way; insulated; red</p>	<a href="http://www.wago.com/859-405/000-005">www.wago.com/859-405/000-005</a>
	<p><b>Item no.: 859-405/000-029</b> Jumper; for jumper slot; 5-way; insulated; yellow</p>	<a href="http://www.wago.com/859-405/000-029">www.wago.com/859-405/000-029</a>
	<p><b>Item no.: 859-405</b> Jumper; for jumper slot; 5-way; insulated; light gray</p>	<a href="http://www.wago.com/859-405">www.wago.com/859-405</a>
	<p><b>Item no.: 859-404/000-029</b> Jumper; for jumper slot; 4-way; insulated; yellow</p>	<a href="http://www.wago.com/859-404/000-029">www.wago.com/859-404/000-029</a>
	<p><b>Item no.: 859-406</b> Jumper; for jumper slot; 6-way; insulated; light gray</p>	<a href="http://www.wago.com/859-406">www.wago.com/859-406</a>
	<p><b>Item no.: 859-405/000-006</b> Jumper; for jumper slot; 5-way; insulated; blue</p>	<a href="http://www.wago.com/859-405/000-006">www.wago.com/859-405/000-006</a>
	<p><b>Item no.: 859-406/000-005</b> Jumper; for jumper slot; 6-way; insulated; red</p>	<a href="http://www.wago.com/859-406/000-005">www.wago.com/859-406/000-005</a>
	<p><b>Item no.: 859-409/000-029</b> Jumper; for jumper slot; 9-way; insulated; yellow</p>	<a href="http://www.wago.com/859-409/000-029">www.wago.com/859-409/000-029</a>
	<p><b>Item no.: 859-410/000-005</b> Jumper; for jumper slot; 10-way; insulated; red</p>	<a href="http://www.wago.com/859-410/000-005">www.wago.com/859-410/000-005</a>
	<p><b>Item no.: 859-410/000-029</b> Jumper; for jumper slot; 10-way; insulated; yellow</p>	<a href="http://www.wago.com/859-410/000-029">www.wago.com/859-410/000-029</a>

Subject to changes. Please also observe the further product documentation!



**Item no.: 859-410**  
Jumper; for jumper slot; 10-way; insulated; light gray

[www.wago.com/859-410](http://www.wago.com/859-410)



**Item no.: 859-410/000-006**  
Jumper; for jumper slot; 10-way; insulated; blue

[www.wago.com/859-410/000-006](http://www.wago.com/859-410/000-006)



**Item no.: 859-403/000-005**  
Jumper; for jumper slot; 3-way; insulated; red

[www.wago.com/859-403/000-005](http://www.wago.com/859-403/000-005)



**Item no.: 859-402/000-029**  
Jumper; for jumper slot; 2-way; insulated; yellow

[www.wago.com/859-402/000-029](http://www.wago.com/859-402/000-029)



**Item no.: 859-403/000-029**  
Jumper; for jumper slot; 3-way; insulated; yellow

[www.wago.com/859-403/000-029](http://www.wago.com/859-403/000-029)



**Item no.: 859-403/000-006**  
Jumper; for jumper slot; 3-way; insulated; blue

[www.wago.com/859-403/000-006](http://www.wago.com/859-403/000-006)



**Item no.: 859-408/000-005**  
Jumper; for jumper slot; 8-way; insulated; red

[www.wago.com/859-408/000-005](http://www.wago.com/859-408/000-005)



**Item no.: 859-408/000-029**  
Jumper; for jumper slot; 8-way; insulated; yellow

[www.wago.com/859-408/000-029](http://www.wago.com/859-408/000-029)



**Item no.: 859-409**  
Jumper; for jumper slot; 9-way; insulated; light gray

[www.wago.com/859-409](http://www.wago.com/859-409)



**Item no.: 859-408/000-006**  
Jumper; for jumper slot; 8-way; insulated; blue

[www.wago.com/859-408/000-006](http://www.wago.com/859-408/000-006)



**Item no.: 859-403**  
Jumper; for jumper slot; 3-way; insulated; light gray

[www.wago.com/859-403](http://www.wago.com/859-403)



**Item no.: 859-409/000-005**  
Jumper; for jumper slot; 9-way; insulated; red

[www.wago.com/859-409/000-005](http://www.wago.com/859-409/000-005)



**Item no.: 859-404**  
Jumper; for jumper slot; 4-way; insulated; light gray

[www.wago.com/859-404](http://www.wago.com/859-404)



**Item no.: 859-409/000-006**  
Jumper; for jumper slot; 9-way; insulated; blue

[www.wago.com/859-409/000-006](http://www.wago.com/859-409/000-006)


Subject to changes. Please also observe the further product documentation!



	<b>Item no.: 859-402/000-006</b> Jumper; for jumper slot; 2-way; insulated; blue	<a href="http://www.wago.com/859-402/000-006">www.wago.com/859-402/000-006</a>
	<b>Item no.: 859-402</b> Jumper; for jumper slot; 2-way; insulated; light gray	<a href="http://www.wago.com/859-402">www.wago.com/859-402</a>
	<b>Item no.: 859-402/000-005</b> Jumper; for jumper slot; 2-way; insulated; red	<a href="http://www.wago.com/859-402/000-005">www.wago.com/859-402/000-005</a>
	<b>Item no.: 859-406/000-006</b> Jumper; for jumper slot; 6-way; insulated; blue	<a href="http://www.wago.com/859-406/000-006">www.wago.com/859-406/000-006</a>
	<b>Item no.: 859-406/000-029</b> Jumper; for jumper slot; 6-way; insulated; signal yellow	<a href="http://www.wago.com/859-406/000-029">www.wago.com/859-406/000-029</a>
	<b>Item no.: 859-407/000-006</b> Jumper; for jumper slot; 7-way; insulated; blue	<a href="http://www.wago.com/859-407/000-006">www.wago.com/859-407/000-006</a>
	<b>Item no.: 859-407/000-005</b> Jumper; for jumper slot; 7-way; insulated; red	<a href="http://www.wago.com/859-407/000-005">www.wago.com/859-407/000-005</a>
	<b>Item no.: 859-407/000-029</b> Jumper; for jumper slot; 7-way; insulated; yellow	<a href="http://www.wago.com/859-407/000-029">www.wago.com/859-407/000-029</a>
	<b>Item no.: 859-407</b> Jumper; for jumper slot; 7-way; insulated; light gray	<a href="http://www.wago.com/859-407">www.wago.com/859-407</a>

**Testing and measuring**

Testing accessories



	<b>Item no.: 859-500</b> WAGO Test pin; 1 mm Ø; 30 V AC / 60 V DC; CAT0; 1 A; 10 mm uninsulated; Test lead for soldering up to 0,5mm <sup>2</sup>	<a href="http://www.wago.com/859-500">www.wago.com/859-500</a>
--	--	--

**Marking accessories**





Marking devices

	<b>Item no.: 210-110</b> Fiber-tip pen	<a href="http://www.wago.com/210-110">www.wago.com/210-110</a>
--	---	--

Marker

	<b>Item no.: 2009-145</b> Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white	<a href="http://www.wago.com/2009-145">www.wago.com/2009-145</a>
	<b>Item no.: 248-501</b> Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white	<a href="http://www.wago.com/248-501">www.wago.com/248-501</a>

Subject to changes. Please also observe the further product documentation!

	<b>Item no.: 248-504</b> Mini-WSB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white	<a href="http://www.wago.com/248-504">www.wago.com/248-504</a>
	<b>Item no.: 248-503</b> Mini-WSB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white	<a href="http://www.wago.com/248-503">www.wago.com/248-503</a>
	<b>Item no.: 248-506</b> Mini-WSB marking card; as card; MARKED; 41 ... 50 (10x); not stretchable; Horizontal marking; snap-on type; white	<a href="http://www.wago.com/248-506">www.wago.com/248-506</a>
	<b>Item no.: 248-502</b> Mini-WSB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white	<a href="http://www.wago.com/248-502">www.wago.com/248-502</a>

## Downloads

### Documentation

#### Bid Text

859-302 docx - Datei	2019 Feb 20	docx 17.1 kB	Download
859-302 X81 - Datei	2019 Feb 19	xml 4.6 kB	Download

#### Instruction Leaflet

CCC Ex (Additional information) 859_***	2023 Apr 26	pdf 135.9 kB	Download
Relay modules, Optocoupler modules	V 2.0.0 2022 Jan 19	pdf 2.1 MB	Download

#### Additional Information

Disposal and Recycling Electrical and electronic equipment, Batteries, Packaging	V 1.1.0 2022 Aug 18	pdf 2.2 MB	Download
---	------------------------	---------------	----------

## CAD/CAE-Data

#### CAE data

EPLAN Data Portal 859-302		URL	Download
WSCAD Universe 859-302		URL	Download

Subject to changes. Please also observe the further product documentation!

ZUKEN Portal 859-302

[URL](#)

[Download](#)

## CAD data

2D/3D Models 859-302

[URL](#)

[Download](#)

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 859-302


[URL](#)

[Download](#)

Relay module; Nominal input voltage: 5 VDC; 1 changeover contact; Red status indicator; Module width: 6 mm; 2,50 mm<sup>2</sup>; gray

## Installation Notes

### Conductor termination



Conductor termination

### Commoning

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27


32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



Easy commoning using adjacent jumpers

### Marking



Marking via Mini-WSB Quick Marking System

Subject to changes. Please also observe the further product documentation!