

Residential/Commercial Combustion Analyzer Kit w/ Printer C165+KIT



Residential/Commercial Combustion Analyzer Kit w/ Printer





10 YEAR WARRANTY





Functions

- Measures: CO (10,000ppm H2 Compensated), CO₂, Differential Pressure, Flue and Inlet Temperature
- Calculates: Differential Temperature, Efficiency (Net, Gross), Excess Air

Features

- Backed by UEi Service+
- Up to 10-Year warranty with annual recertification
- LINK to wireless probes
- Wireless Flow and Return Probes
- NOx filtered & H2 Compensated CO sensor (10,000ppm range)
- Over-range protection pump
- NOx filtered CO sensor
- Low Flow Detection to protect reading accuracy
- Compatible with DTHA2
- Room CO test
- Differential Pressure
- Heat Exchanger test
- Protective water trap
- Wireless connection to a Free Printer App (iOS® and Android™ Compatible)



LINK to wireless Flow and Return pipe clamp probes.





Includes

- Flue Probe (CP2)
- IR Thermal Printer (IRP-2)
- Printer Paper Roll (spare) (16646)
- Rechargeable Batteries 3 (AA)
- USB Charging Cable (AACA5)
- Wireless Pipe Clamp Probes 2 (WPC2)
- Tubing w/ connector (11000)
- K-Type Thermocouples 2 (ATT29)
- Particle Filter (spare) (17631)
- Carrying Case (AC509)
- Quick Start Guide











Residential/Commercial Combustion Analyzer Kit w/ Printer



C165+KIT

Specifications

TEMPERATURE MEASUREMENT

| Parameter | Range | Resolution | Accuracy |
|--|---------------|------------|--------------------------|
| Flue temperature | 32° to 1112°F | 0.1°F | ±(0.3% rdg +3.6°F (2°C)) |
| Inlet temperature (internal sensor) | 32° to 112°F | 0.1°F | +1.8°C +0.3% rdg |
| Inlet temperature (external sensor) | 32° to 1112°F | 0.1°F | +3.6°F +0.3% rdg |

FLUE GAS

| Parameter | Range | Resolution | Accuracy |
|---------------------------|-----------------|------------|---------------------|
| Oxygen | 0 to 21% | 0.1% | +0.3% Volume |
| Carbon Monoxide | 0 to 2000ppm | 1ppm | ±3ppm or ±5% of rdg |
| | 2000 to 9999ppm | | ±10% of rdg |
| | Above 9999ppm | | Unspecified |
| Carbon Dioxide | 0 to 20% | 0.1% | 0.3% rdg |
| Efficiency (Net or Gross) | 0 to 99.9% | 0.1% | +1.0% rdg |
| Efficiency High (C) | 0 to 119.9% | 0.1% | +1.0% rdg |
| Excess Air | 0 to 250% | 0.1% | +0.2% rdg |
| CO/CO2 ratio | 0 to 0.999% | 0.0001 | +5% rdg |

PRESSURE (DIFFERENTIAL)

| Parameter | Range | Resolution | Accuracy |
|-------------------------|---------|------------|-----------|
| Pressure (Differential) | ±80mbar | 0.1mbar | ±0.5% FSD |

| PRE-PROGRAMMED FUELS Natural Gas, Propane, Butane, LPG, Light Oils (28/35sec), Wood Pellets, Town Gas, Coke Gas, Bio Oil, Bio Gas |
|--|
|--|

| USER PROGRAMMED FUELS | 5 User defined fuels |
|-----------------------|----------------------|

| STORAGE CAPACITY | 30 tests |
|------------------|----------|

Downloads



Manual



Data Sheet



