

## SUMMARY

### # Wires

Low voltage 6



*Image is for illustrative purpose only*

Series 2P  
Termination type Male solder  
IP rating 66  
AWG wire size 28.00 - 20.00  
Cable Ø 5.30 - 7.20 mm  
Status active  
Matching parts [CNB.M06.GLLA](#)

### Download

[Request a quote](#)

[Catalog](#)

## TECHNICAL DETAILS

### Mechanics

Shell Style/Model CF\*: Straight plug with cable collet, watertight (IP 66) and nut for fitting a bend relief  
Keying 3 keys (alpha=0, gamma=60; Plug: male contacts; Receptacle: female contacts)  
Housing Material PSU (Polysulfone), gray  
Weight 9.35 g

### Performance

Configuration 2P.M06 : 6 Low V.  
Insulator L: PEEK for solder contacts  
Rated Current 12 Amps

### Specifications


Contact Type: Solder  
Contact Dia.: 1.3 mm (0.051in)  
Bucket Dia.: 1.1 mm (0.043in)  
Test voltage (kV rms) Contact-contact: 1.35  
Air clearance min.: 1.2 mm  
Creepage distance min.: 1.2 mm

### Others

*LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*

Endurance (Shell): >1000 mating cycles  
 F ret (min): 150 N  
 F ret (max): 250 N  
 Steam sterilization: 20 times (with potting on rear connection)

## DRAWINGS



### Dimensions

	A	L
mm.	18	57
in.	0,71	2,24

## RECOMMENDED BY LEMO

### Tools

### Cables

CMN.06.T20.062PGZE		Grey	
CMN.06.T20.062PNZE			
CMN.06.T20.062QGZE	TPR (medical)	Grey	
106220	PVC	Black	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

12080	PVC	Grey	
160240	PVC	Black	
260250	PVC	Grey	

*LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.*