

## Coaxial Cable Connector 24\_TNC-50-4-52/133\_N

### Description

Straight bulkhead cable feed through

Interface standards

IEC 60169-17\_MIL-STD-348A/313\_CECC 22200

### Technical Data

#### Electrical Data

Impedance	50 Ω	
Interface frequency max.	15 GHz	
Frequency range	DC to 11 GHz	11 to 15 GHz
Return loss	21 dB	15 dB

#### Mechanical Data

Centre contact	plugged
Outer contact	crimped
Weight	0.0212 kg

#### Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating
Crimp ferrule	Copper	SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00009244
Assembly instruction	DOC-0000179057
Mounting hole	DOU-00008751

### Ordering Information

Single package	24_TNC-50-4-52/133_NE
----------------	-----------------------

### Additional Information

Suitable cables	S_04272_B, S_04172_D
-----------------	----------------------