

## Specification Sheet

Part Number: T18I9C2



Cable Tie, 5.5" Long, UL Rated, 18lb Tensile Strength, PA66, Natural, 100/pkg

<b>Article Number</b>	111-02311
<b>Type</b>	T18I
<b>Color</b>	Natural (NA)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Inside serrations allow for strong grip on cables and wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force.</li><li>• Bent tail ensures a quick and simple installation.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
<b>Short Description</b>	Cable Tie, 5.5" Long, UL Rated, 18lb Tensile Strength, PA66, Natural, 100/pkg

Global Part Name

T18I-PA66-NA

Minimum Tensile Strength (Imperial)

18.0

Minimum Tensile Strength (Metric)

80.0

Length L (Imperial)

5.5

Length L (Metric)

139.7

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.10

Width W (Metric)

2.5

Bundle Diameter Min (Imperial)

0.06

Bundle Diameter Min (Metric)

1.5

Bundle Diameter Max (Imperial)

1.38

Bundle Diameter Max (Metric)

35.0

<b>Material</b>	Polyamide 6.6 (PA66)
-----------------	----------------------

<b>Material Shortcut</b>	PA66
--------------------------	------

<b>US MIL SPEC</b>	MS3367-4-9	<b>Flammability</b>
--------------------	------------	---------------------

UL 94 V2	<b>Halogen free</b>
----------	---------------------

Yes	<b>Operating Temperature (Metric)</b>
-----	---------------------------------------

-40°F to +185°F (-40°C to +85°C)	<b>Reach Complaint(Article 33)</b>
----------------------------------	------------------------------------

Yes	<b>ROHS Complaint</b>
-----	-----------------------

Yes	<b>Certification/Specification WEB</b>
-----	--

DNV GL   IEC 62275:2006	<b>UL Recognized (US)</b>
-------------------------	---------------------------

Yes	<b>UL Listed (US and Canada)</b>
-----	----------------------------------

Yes	<b>UL Recognized (US and Canada)</b>
-----	--------------------------------------

Yes	<b>UL Listed (US)</b>
-----	-----------------------

Yes

<b>Package Quantity(Imperial)</b>	100
-----------------------------------	-----

<b>Package Quantity (Metric)</b>	100
----------------------------------	-----

<b>Customs Number</b>	3926909988
-----------------------	------------

<b>Content Unit(BMEcat)</b>	pcs.
-----------------------------	------

---

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)