




MT8/8-CC2WA-AN

Ruland Adjustable Two-Way Connector Clamp, Thru Holes 8mmx8mm, L 52.5mm, W 16mm, Black Anodized Aluminum





Description

Ruland MT8/8-CC2WA-AN an adjustable two-way connector clamp with thru holes for 8mm round tubes, M4 clamp screws, 16mm width and height, and 52.5mm overall length. It is designed to fit on Ruland tubes and flange bolt bases that begin with MT8. MT8/8-CC2WA-AN is aluminum with a black anodized finish and screws are 304 stainless steel for added corrosion resistance when compared to unplated types. This two-way adjustable connector clamp is commonly used to support tubes for mounting sensors, screens, reflectors, plexiglass machine guards, and other industrial components. It is designed for applications where frequent angular adjustments are needed such as machine diagnostic screens. When paired with MT8-ALK-M4-16 adjustable clamping levers the user can rapidly reposition the screen angularly and/or vertically without tools providing for a safer and more comfortable working environment for the employee and helping to increase productivity. MT8/8-CC2WA-AN is manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

i roddot opcomodtions			
Thru Hole 1 Diameter B1	8 mm	Thru Hole 2 Diameter B2	8 mm
Thru Hole Tolerance	+0.09/-0 mm	Thru Hole 2 Tolerance	+0.09/-0 mm
Width & Height W1	16 mm	Width and Height 2 W2	16 mm
Edge to Center 1 L2	13 mm	Edge to Center 2 L3	13 mm
Center To Center LC	26.5 mm	Overall Length L1	52.5 mm
Clamp Screw CL	M4	Set Screw SS	M4
Weight (lbs)	0.075800	Material Specification	Anodized Aluminum
Manufacturer	JW Winco/ Otto Ganter	UPC	634529231807
Country of Origin	Germany	Tariff Code	7609.00.0000
UNSPC	31162908		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
Prop 65	▲WARNING This product can expose you to the chemical Nickel (metallic), known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov .		