

## Specification Sheet

Part Number: T120R0PPH4



Cable Tie, 15.2" Long, 60lb Tensile Strength, PP, Black, 500/pkg

**Article Number**

111-12066

**Type**

T120R

**Color**

Black (BK)

**Features & Benefits**

- Polypropylene cable ties deliver excellent resistance to chemicals and salts.
- Inside serrations provide strong grip on cables and wire bundles.
- Easy application either manually or with a tensioning tool.
- Bent tail ensures a quick and simple installation.

**Quantity Per**

bag

**Product Description**

HellermannTyton's polypropylene cable ties offer added resistance to most chemicals. T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Cable Tie, 15.2" Long, 60lb Tensile Strength, PP, Black, 500/pkg
<b>Global Part Name</b>	T120R-PP-BK
<b>Minimum Tensile Strength (Imperial)</b>	60.0
<b>Minimum Tensile Strength (Metric)</b>	267.0
<b>Length L (Imperial)</b>	15.2
<b>Length L (Metric)</b>	387.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.30
<b>Width W (Metric)</b>	7.6
<b>Bundle Diameter Min (Imperial)</b>	0.20
<b>Bundle Diameter Min (Metric)</b>	5.0
<b>Bundle Diameter Max (Imperial)</b>	4.1
<b>Bundle Diameter Max (Metric)</b>	104.1
<b>Thickness T (Imperial)</b>	0.07

**Thickness T (Metric)** 1.8

**Material** Polypropylene (PP)

**Material Shortcut** PP

**Flammability** UL 94 HB

**Halogen free** Yes

**Operating Temperature (Metric)** -40°F to +239°F (-40°C to +115°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 500

**Package Quantity (Metric)** 500

**Customs Number** 3926909988

**Content Unit(BMEcat)** pcs.

**Weight (Metric)** 5.2

