

Material Safety Data Sheet

1 of 3

Product: Daburn Stretch-N-Seal™ Tape

I. PRODUCT DESCRIPTION

Trade Name/Synonyms Butyl Rubber (IIR), Stretch-N-Seal™, Magic Wrap, Safety Wrap
CAS Registered Name: 1,3 Butadiene, 2 methyl-,polymer with 2 methyl-propane
CAS Registry Number 9010-85-9 Family Name Butyl Rubber
WHMIS Classification Not classified (Non hazardous)
Chemical Formula (C5H8.C4H8)x Emergency Phone: (519) 899-2352

II. INGREDIENTS

<u>Ingredient</u>	<u>CAS Name</u>	<u>Concentration</u>
Isobutylene-isoprene copolymer	901076	100 Percent
Common Compounding	N/AP	N/AV

III. FREE MONOMERS

N/AV

IV. PHYSICAL DATA

Physical State:	Solid, roll of tape	Volatility @ 105°C (wt. %) N/AV
Odor:	Odorless	Ash @ 550°C)wt. %)
Appearance:	Black	Bulk Density N/AP
Specific Gravity	0.96	

V. FIRE AND EXPLOSION

Flammable / Combustible: No If yes under what Conditions: See Section XI
Extinguishing Media: Carbon dioxide, foam, water spray
Special Fire Fighting Instructions: Treat as a hydrocarbon fire. Use self contained breathing apparatus.
Flashpoint & Method: Above 300°C (COC)
Lower Explosive Level: N/AP (% volume)
Upper Explosive Level: N/AP
Hazardous Combustion Products: Carbon monoxide, carbon dioxide and hydrocarbons

VI. REACTIVITY DATA

Chemically Stable: Yes If no under what conditions: N/AP
Incompatible with other substances: No If yes which ones: N/AP
Conditions of reactivity: Will not polymerize
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide and hydrocarbons

2 of 3

Material Safety Data Sheet

Product: Stretch-N-Seal™ Tape

VII. PREVENTATIVE MEASURES

Personal protective equipment

Respiratory: Not required Skin: Gloves not required Eye: Safety glasses
Footwear: Approved foot wear
Storage: Below 35°C, in dry area and in the absence of direct natural or artificial light
Self Life: 60 months
Possible change on storage: Not Determined Engineering Controls: None required
Spill & Leak Procedures: Repackaged uncontaminated product
Waste Disposal: Bury in approved landfill site in accordance with municipal provincial and federal regulations

VIII. FIRST AID MEASURES

Skin: After repeated or prolonged contact, wash thoroughly with warm water and mild soap

Eye: Flush immediately with water for at least 15 minutes. Obtain medical attention immediately

Inhalation: Unlikely

Ingestion: Unlikely

IX. TOXICOLOGY

No testing has been carried out. However, Daburn believes this product is an inert solid at ambient temperatures.

X. CONFORMITY TO TRANSPORTATION, HEALTH SAFETY AND FOOD REGULATIONS

Transportation Canada:	This product is not regulated under the Canadian Transportation of Dangerous Goods Regulations
Transportation USA	This product is classified as non-hazardous according to the US Department of Transportation CFR, Title 49
Occupational Health	This product is non hazardous according to the US OSHA Hazard Communication Standard, 29 CFR 1910.1200 or any State or Municipality "Right to Know" regulations
Compliance to Food Regulations:	None
WHMIS Classification:	This product is non-hazardous
State of California Proposition 65, 1986	This product is non-hazardous does not require labeling
Other:	N/AV

3 of 3

Material Safety Data Sheet

Product: Stretch-N-Seal™ Tape

XI. ADDITIONAL INFORMATION

Note 1: This product can burn but does not meet recognized flammable and combustible flash point definitions.

XII. PREPARED BY

Daburn Electronics and Cable Corp.
224 Pegasus Avenue
Northvale, NJ 07647
Telephone number: (201) 767-5400
Fax number (201) 768-9642

Date of Preparation: November 25, 1995

For additional information or copies of this MSDS contact:

Daburn Electronics and Cable Corp.
224 Pegasus Avenue

Northvale, NJ 07647