

Specification Sheet

Part Number: 181-34000



Solid Wall Wiring Duct, 3" x 4", Non-Adhesive, PVC, Gray, 120ft/Carton

| | |
|--------------------------------|---|
| Article Number | 181-34000 |
| Type | SD3X4 |
| Color | Gray (GY) |
| Features & Benefits | <ul style="list-style-type: none">•Solid wall construction provides excellent coverage to keep wires clean.•Durable material protects wires from damage, with long-lasting performance.•Available standard colors complement or contrast in light and dark environments.•Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration. |
| Quantity Per | carton |

Product Description

HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct is designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6 foot lengths.

| | |
|---|--|
| Short Description | Solid Wall Wiring Duct, 3" x 4", Non-Adhesive, PVC, Gray, 120ft/Carton |
| Global Part Name | SD3X4-PVC-GY |
| Technical Description | Non-Adhesive |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 1.83 |
| Width W (Imperial) | 3.0 |
| Width W (Metric) | 76.2 |
| Height H (Imperial) | 4.07 |
| Height H (Metric) | 103.4 |
| Mounting Hole Centers (Imperial) | 4.0 |
| Material | Polyvinylchloride (PVC) |
| Material Shortcut | PVC |
| Flammability | Self-Extinguishing |
| Halogen free | No |
| Operating Temperature (Metric) | +122°F (+50°C) |

Reach Complaint(Article 33)

No

ROHS Complaint

Yes

Certification/Specification WEB

EN 50085-2-3_1A CSA UL EN 50085-1:2005 + A1:2013

UL Recognized (US)

Yes

Package Quantity(Imperial)

120

Package Quantity (Metric)

36.58

Customs Number

3925900000