

X-Lok IP68 Screw-In Terminal Field Installable

Easy Wiring And Quick Blind Mates

Amphenol LTW is proud to introduce our latest X-Lok Field Installable in Screw-in Terminals version with IP68 rated ingress protection enabling convenient repair, maintenance and installation services. The X-Lok family offers fast & secure interconnect with audible feedback and guided key for blind mating substituting conventional box wiring for AC / DC.



Applications:




Renewable Energy Solar Power



Broadband Wireless Access



Heavy Vehicle



*MM- Male Conn. Male Pin *FF- Female Conn. Female Pin

*MF- Male Conn. Female Pin *FM- Female Conn. Male Pin



Handling Specification:

Lift & Materials

•				
Current Rating	20A	Cable OD for Different Seals	C Size	Small Seal: 6.0~8.0mm Middle Seal: 8.0~10.0mm Large Seal: 10.0~12.0mm
Voltage Rating	300 V AC/DC (Power)			
Temperature Range	-40 °C ~ 105°C		D Size	Small Seal: 8.0~10.0mm Middle Seal: 10.0~12.0mm Large Seal: 12.0~14.0mm
Waterproof Rating	IEC60529, IP68 (1m/24hrs)			
Torque Force	For Clamp Ring: 6-8 Kgf For Sealing Nut: 8-15Kgf For Screw: 4-5Kgf		Housing	Thermoplastic, UL Recognized
		Material	Contact	Copper Alloy, Silver Plated
Safety Compliance	UL 1977		Seal	Rubber, UL Recognized
Recommended Wire Gauge	20A: 14AWG ~ 12AWG			

Luc Kan | Sales & Marketing | Email: luc@ltw-tech.com

Find out more Follow us on new product here





