


**ENERGIZER 346**

**ZEROMERCURY**

**SILVER OXIDE**



**Industry Standard Dimensions**




**Specifications**

- Chemical System:** Silver Oxide (Zn/Ag<sub>2</sub>O)
- Nominal Voltage:** 1.55 Volts
- Typical Capacity:** 9.5 mAh\* (to 1.2 volts)
- Capacity Test:** 100K ohm continuous drain at 21°C
- Typical Weight:** 0.24 grams (0.008 oz.)
- Typical Volume:** 0.06 cubic centimeters (0.003 cubic inch)
- Impedance (40 Hz):** 30 to 40 ohms

\* Varies according to the applied load, temperature, and cutoff voltage.

**Cross Section**




DESIGNED FOR USE ON CONTINUOUS LOW DRAIN

**Typical Discharge Characteristics**

Typical Performance at 21°C (70°F)

**Schedule:** Continuous  
**Typical Drain @1.55V:**  
 0.016 milliamperes  
**Load:** 100K ohm




<b>Schedule</b>	<b>Typical Drains at 1.55V (milliamperes)</b>	<b>Load (ohm)</b>	<b>Cutoff (hours)</b>
Continuous	0.016	100K	594


**Temperature Characteristics**

Typical Performance at Low Discharge Rates

**Service Effects**



**Storage Effects**



**Important Notice**

This datasheet contains typical information specific to products manufactured at the time of its publication.  
**Contents herein do not constitute a warranty and are for reference only.**