

Specification Sheet

Part Number: FEWM24



- Durable stainless steel construction for long life.
- Cable management spools for effective slack management.
- Bend radius control to minimize hand and wrist strain.
- Smooth grommet entry to protect cables from damage.
- Meet ANSI/TIA/EIA 568-C standards.

Wall Mount Fiber Enclosure, Unloaded, accepts 4 Adapter Panels, 2 Splice Trays, Black, 1/pkg

Article Number 904-00685

Type FEWM24

Color Black (BK)

Quantity Per box

Product Description HellermannTyton wall mount and rack mount fiber enclosures provide durable protection for direct termination and splice LAN applications. Capable of supporting up to 2,304 fibers, our enclosures are equipped with cable management and routing accessories to control cable slack, limit bend radius and add strain relief control. Additional cable management spools, splice trays and splice sleeves are available for added convenience and versatility. HellermannTyton offers wall mount and rack mount fiber enclosures that work in a standard LGX footprint

Short Description	Wall Mount Fiber Enclosure, Unloaded, accepts 4 Adapter Panels, 2 Splice Trays, Black, 1/pkg
Global Part Name	FEWM24-MET-BK
Technical Description	HellermannTyton wall mount fiber enclosures provide a secure termination solution for LAN applications requiring fully enclosed and/or lockable enclosures. Wall mount enclosures accommodate up to 144 fibers, mount easily and provide easy cable routing access behind the enclosure. Choose from enclosure options to accommodate 1, 2 or 4 standard LGX-style adapter panels.
Port Count	24 96 48
Length L (Imperial)	3.5
Length L (Metric)	88.9
Variant	Wall mount
Width W (Imperial)	15.0
Width W (Metric)	381.0
Height H (Imperial)	15.63
Height H (Metric)	397.0
Depth D (Imperial)	3.7
Depth D (Metric)	93.98

Material Metal (MET)

Material Shortcut MET

Package Quantity (Imperial) 1

Package Quantity (Metric) 1

Customs Number 8538907080