



! Cable reel, 50 m,  
available on request.  
Part Nr. 7100.2000.TR50



Clip-on humidity and temperature sensor



Barcode scanner



Video

Metriso® 3000 - test kit includes: digital high resistance tester, temperature and relative humidity sensor, USB port, PC software ETC for Windows®, 2 probes, a hand-held probe with connecting cable, user's instructions in German, English and French, calibration certificate, conductive carrying case fitted with dissipative pink foam.

- Suitable for resistance point-to-point and resistance to ground measurements
- Integrated data logger with USB communication port for data transmission (50.000 test values). The supplied Report Generating Software ETC allows to generate a complete test report
- Clip-on humidity and temperature sensor
- A barcode scanner can be used in order to record test points before testing

- Test voltage / Test current:  $1 \text{ mA} \leq I \leq 1,3 \text{ mA}$
- Test range:
 

High ohmic range:	DC 10 volts, 100 volts and 500 volts
low ohmic range:	1 Ohm to 9,99 kOhm
High ohmic range:	1 kOhm to 1,2 TOhm
- Operation: Battery operated
- Probes:
 

2 x Model 850	(weight: 2,27 kg / Ø 63,5 mm)
1 x hand-held probe Model 45	

complies with  
IEC 61340-4-1, IEC 61340-2-3, IEC 61340-4-5

IEC  
EN

#### Part Nr.

<b>7100.3000.MK</b>	Metriso® 3000 Test Kit, menu language German/English/French/Spanish
<b>7100.3000.MK.870</b>	Metriso® 3000 Test Kit with Probes 870, menu language German/English/French/Spanish
<b>7100.3000.G</b>	Metriso® 3000 Test Instrument only, menu language German/English/French/Spanish

#### Accessories

<b>7100.2000.TR50</b>	50 m extension cable for floor measurements
<b>7100.2000.ML</b>	Replacement set of connecting cables (com/shield, +pole)
<b>7100.3000.SC.2D</b>	Barcode-Scanner for 2D and 1D Codes
<b>7100.3000.Z502H</b>	Rechargeable battery pack 8 x NiMH
<b>7100.3000.Z502R</b>	Charger unit for rechargeable battery