



SS Stainless Steel

3 Type

- E** With tapped blind bore
- D** With tapped through bore
- C** With plain blind bore, tol. H7

Specification



- Stainless steel precision casting
- European Standard No. 1.4308 (AISI CF-8)
 - Matte shot-blasted finish **MT**
 - Highly polished finish **PL**
(only available in Types D, E in metric sizes)
- RoHS compliant

On request

- Version with convex top and sides in highly polished finish
- Polished finish available for inch size tapped knobs
- Other modifications such as inch or metric tapped holes, blind or through bores, cross holes, set screw holes and threaded studs

Information

GN 5339.5 triangular knobs were specially designed for use on machinery in the food industry. The smooth and enclosed areas as well as the corner radii comply with the requirements of hygiene standards.

With an elegant ergonomical design, these knobs also withstand a relatively high torque.

see also...

- Star Knobs GN 5334 (Stainless Steel)
- Star Knobs DIN 6336 (Stainless Steel)
- Hand Knobs DIN 6335 (Stainless Steel)
- Star Knobs GN 5335 (Stainless Steel)
- Wing Nuts GN 834 (Stainless Steel)

How to order (Inch)	1 Handle diameter d_1
GN 5339.5-32-10X32-E-MT	2 Thread d_2
	3 Type
	4 Finish

How to order (Metric)	1 Handle diameter d_1
GN 5339.5-50-M10-D-PL	2 Thread d_2 (Bore d_s)
	3 Type
	4 Finish

Inch table

Dimensions in: inches - millimeters

d₁	d₂ Thread Type E	d₄	h₁ ≈	h₂ ≈	t₁ min.
1.26 32	10 x 32	.47 12	.83 21	.47 12	.39 10
1.26 32	1/4 x 20	.47 12	.83 21	.47 12	.47 12
1.57 40	1/4 x 20	.55 14	1.02 26	.55 14	.47 12
1.57 40	5/16 x 18	.55 14	1.02 26	.55 14	.59 15
1.97 50	5/16 x 18	.71 18	1.30 33	.75 19	.59 15
1.97 50	3/8 x 16	.71 18	1.30 33	.75 19	.71 18
2.36 60	3/8 x 16	.79 20	1.61 41	.91 23	.71 18
2.36 60	1/2 x 13	.79 20	1.61 41	.91 23	.87 22

Metric table

Dimensions in: millimeters - inches

d₁	d₂ Thread Type E	Type D	d₃ H7 Bore Type C	d₄	h₁ ≈	h₂ ≈	t₁ min.	t₂
32 1.26	M 5	-	-	12 .47	21 .83	12 .47	10 .39	-
32 1.26	M 6	M 6	B 6	12 .47	21 .83	12 .47	12 .47	10 .39
40 1.57	M 6	-	-	14 .55	26 1.02	14 .55	12 .47	-
40 1.57	M 8	M 8	B 8	14 .55	26 1.02	14 .55	15 .59	13 .51
50 1.97	M 8	-	-	18 .71	33 1.30	19 .75	15 .59	-
50 1.97	M 10	M 10	B 10	18 .71	33 1.30	19 .75	18 .71	16 .63
60 2.36	M 10	-	-	20 .79	41 1.61	23 .91	18 .71	-
60 2.36	M 12	M 12	B 12	20 .79	41 1.61	23 .91	22 .87	20 .79

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4

