



Circular Connectors IP68
Circular Connectors AC 167 micro
AC 167 REST/2 M16



panel mount plug, 2 pole, voltage rating: 500 V, current rating: 10 A

Order Info

| | |
|-----------------------------------|---------------|
| reference number (ref.no.) | 72876216 |
| PU | 200 |
| EAN | 4028012133833 |

Type

| | |
|--|---------------------|
| type | panel mount plug |
| number of poles | 2 pole |
| clamping units per pole | 1 |
| colour | black |
| coding | 1 (mains) |
| cross-section rating | 1.0 mm ² |
| connection type | screw |
| protection against incorrect plugging | yes |
| latch | yes |

Technical Data

| | |
|---|----------------------|
| voltage rating | 500 V |
| current rating | 10 A |
| impulse voltage rating | 4.0 kV |
| insulating material | PA 6.6 |
| contact material | brass |
| core cross-section min. | 0.25 mm ² |
| core cross-section max. | 1.0 mm ² |
| protection class | SK II |
| flammability rating | V-0 |
| max. ambient temperature operation | 60 °C |
| IP code | IP66/IP68/IP69 |
| type of conductor solid | yes |
| type of conductor flexible | yes |
| type of conductor stranded | yes |
| stripping length | 10.0 mm |
| dismantling length | 20.0 mm |

| | |
|-------------------------------|-------------------------|
| assembly contact screw | M2 - max. τ 0,2 Nm |
|-------------------------------|-------------------------|

| | |
|----------------------------|--------|
| wall thickness max. | 7.0 mm |
|----------------------------|--------|

| | |
|------------------------------|-----|
| housing hole diameter | M16 |
|------------------------------|-----|

| | |
|-----------------------------------|--------|
| tightening torque lock nut | 1,5 Nm |
|-----------------------------------|--------|

Accessories

| | |
|------------------------|--------|
| AC 167 RVKS M16 | 729042 |
|------------------------|--------|

| | |
|---------------------|--------|
| AC 167 RWZ/2 | 729044 |
|---------------------|--------|