



CIRCUIT: SPST
CONTACT CONFIGURATION

RECOMMEND P.C.B. LAYOUT

NOTES:

1. ALL DIMENSIONS IN MM
2. TERM. NOS. FOR REF ONLY
3. RATING: 50mA, 12V DC
4. TRAVEL: 0.25±0.1mm
5. OPERATING FORCE: 160±50gf
6. CONTACT RESISTANCE: 100mOHMS MAX.
7. DIELECTRIC STRENGTH: 250V RMS MIN
8. ELECTRICAL LIFE: 100,000 CYCLES MIN
9. ▲ DENOTES CRITICAL PARAMETER
10. 2002/95/EC (ROHS) COMPLIANT

| | | | | |
|------|-------|--------------------------|---------|------|
| C | 18677 | LEG TOLERANCE WAS +/-0.1 | 10/9/09 | BLR |
| B | | ADD GOLD DOME NOTE | 6/5/06 | CT |
| A | | RELEASED FOR PRODUCTION | | |
| REV. | PCR | DESCRIPTION | DATE | CHKD |

| TOLERANCES | |
|------------|-------|
| 0.0 | ±0.4 |
| 0.00 | ±0.25 |

| | | | | |
|-----------|-----------------|-----------------|---------|-----|
| SCALE | DATE | DR | DWG | REV |
| 4:1 | 10/9/09 | BLR | P010323 | C |
| TITLE | TL 1105V F160 R | | | |
| E-SWITCH® | | LAMB INDUSTRIES | | |

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED