



## Screw-Screwless Connectors

### 900 Q/ 3

terminal block, 3 pole, fixing: screw, clamping units per pole: 4, voltage rating: 450 V, current rating: 17.5 A, cross-section external: 2.5 mm<sup>2</sup>, cross-section internal: 1.5 mm<sup>2</sup>



### Order Info

<b>reference number (ref.no.)</b>	114003
<b>PU</b>	800
<b>EAN</b>	4028012104321

### Type

<b>type</b>	terminal block
<b>number of poles</b>	3 pole
<b>clamping units per pole</b>	4
<b>colour</b>	white
<b>cross-section rating</b>	1.5 / 2.5 mm <sup>2</sup>
<b>connection type</b>	screw-screwless

### Technical Data

<b>voltage rating</b>	450 V
<b>current rating</b>	17.5 A
<b>insulating material</b>	PA
<b>contact material</b>	brass
<b>flammability rating</b>	V-2
<b>max. ambient temperature operation</b>	85 °C
<b>assembly contact screw</b>	0,8x4,0 / ⚙ 0,5 Nm
<b>internal core cross-section min.</b>	0.5 mm <sup>2</sup>
<b>internal core cross-section max.</b>	1.5 mm <sup>2</sup>
<b>internal stripping length</b>	7.0-7.5 mm
<b>external stripping length</b>	8.0-8.5 mm
<b>fixing</b>	screw
<b>type of conductor solid external</b>	yes
<b>type of conductor flexibel external</b>	yes
<b>type of conductor solid internal</b>	yes
<b>type of conductor stranded internal</b>	yes
<b>cross-section external</b>	2.5 mm <sup>2</sup>
<b>cross-section internal</b>	1.5 mm <sup>2</sup>
<b>ammonia resistance</b>	yes

## Approvals

---

<b>acc. to EN 60998</b>	<a href="#">Download PDF</a>
<b>acc. to UL</b>	<a href="#">Download PDF</a>
<b>acc. to CSA</b>	<a href="#">Download PDF</a>

---

## Accessories

---

<b>ZEL 110</b>	196420
----------------	--------

---