
# Cabinet "U" Handles

Round Steel, with Tapped Holes









## **Metric table**

<b>U</b>										Dimensions in: millimeters - inches			
d <sub>1</sub>	Length   ±0	Length I ±0.5								h	r	t min.	
6 .24	32 1.26	45 1.77	55* 2.17	64 2.52	88 <b>*</b> 3.46	-	-	M 3	9 .35	26 1.02	7 .28	7 .28	
8 .31	55 <b>*</b> 2.17	64 2.52	88 <b>*</b> 3.46	96 <i>3.7</i> 8	100 3.94	120 <b>*</b> 4.72	128 5.04	M 4	12 .47	35 1.38	10 .39	8 .31	
10 .39	88 <b>*</b> 3.46	100 3.94	120 <b>*</b> 4.72	180 <b>*</b> 7.09	200 7.87	235 <b>*</b> 9.25	-	M 5	15 .59	43 1.69	12 .47	12 .47	
12 .47	125 4.92	160 <i>6.30</i>	200 7.87	250 9.84	-	-	-	M 6	-	51 2.01	14 .55	12 .47	
16 .63	160 <i>6.30</i>	200 7.87	250 9.84	300 11.81	-	-	-	M 6	-	59 2.32	18 .71	12 .47	

<sup>\*</sup> Suitable for 19" rack and enclosure layout

### Specification

- Steel
- Powder coated Black, RAL 9005, textured finish
- Chrome-plated finish
- Blackened finish
- Location disks
  Zinc die-cast, nickel-plated finish
- RoHS compliant

### On request

- Various metric size fasteners and kit packaging
- For certain minimum quantities, other lengths according to customer requirements

#### Information

3

SW

**OCR** 

**BT** 

GN 425 cabinet "U" handles are manufactured from a bent steel profile. Cabinet "U" handles with Ø  $d_1 = 6$ , 8 and 10 mm are supplied with two location disks to guarantee a perfect location even with large holes in the cabinet. The location disks are enclosed in the package with the handle.

The manufacturing process allows the production of special lengths in relatively small quantities.

The chrome-plated design is only conditionally suitable for outdoor use. The GN 425 stainless steel design should be given preference for constant outdoor use.

#### see also...

- Cabinet "U" Handles GN 425 (Round Stainless Steel)
- Cabinet "U" Handles GN 425.1 (Offset Round Steel)

How to order	1 Handle diameter d <sub>1</sub>	
<b>1</b> 5 3	2 Length I	
GN 425-10-120-CR	3 Finish	