

Null Modem Serial DB9 Serial Cable (DB9 to DB25 F/M), 6 ft. (1.83 m)

MODEL NUMBER: P456-006







Highlights

- Superior molded cables with foilshielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Null modem cables connect two serial devices that require a null modem configuration

System Requirements

 Two serial devices (one with a DB25 Male connector and the Other with a DB9 Female connector) requiring a null modem (cross-wired) configuration.

Package Includes

• 6-ft. (1.83 m) Null Modem Gold Cable DB9F to DB25M

Description

Null modem cables and adapters connect two serial devices that require a null modem (cross-wired) configuration. This 6-ft. (1.83 m) cable has a DB9 female connector on one end and a DB25 male connector on the other. Superior molded cables with foil-shielding offer maximum EMI/RFI protection. Gold-plated connectors and contacts provide superior conductivity.

Features

- DB9 female to DB25 male
- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- · Gold-plated connectors provide superior conductivity

Specifications

| OVERVIEW | | |
|---------------------------------|----------------------|--|
| UPC Code | 037332013354 | |
| PHYSICAL | | |
| Color | Black | |
| Cable Jacket Color | Black | |
| Cable Length (ft.) | 6 | |
| Cable Length (m) | 1.83 | |
| Shipping Dimensions (hwd / in.) | 8.50 x 6.90 x 0.50 | |
| Shipping Dimensions (hwd / cm) | 21.59 x 17.53 x 1.27 | |
| Shipping Weight (lbs.) | 0.37 | |



| Shipping Weight (kg) | 0.17 | |
|-------------------------------------|---------------------------|--|
| 11 0 0 0 | | |
| CONNECTIONS | | |
| Side A - Connector 1 | DB9 (FEMALE) | |
| Side B - Connector 1 | DB25 (MALE) | |
| STANDARDS & COMPLIANCE | | |
| Product Compliance | RoHS | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.