

HEIDI-O

~50° x 11° oval beam

SPECIFICATION:

Dimensions	Ø 21.6 mm
Height	11.7 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish
HEIDI-O	Single lens	PMMA	clear	
HEIDI-TAPE	Tape	Acrylic foam	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA12949_HEIDI-O	Single lens	3264	204	204	11.1
» Box size: 480 x 280 x 300 mm					





This drawing is our property. It can't be reproduced or communicated without our written agreement.



Ledil Oy
 Joensuunkatu 13
 FIN-24100 SALO
 Finland

DRAWN BY ah		DATE 1.2.2012	DRAWING TITLE Datasheet Heidi-Series Assy		
CHECKED BY	DATE	SIZE A4	DRAWING NUMBER	REV 2	
DESIGNED BY	DATE	SCALE 2:1	WEIGHT (g)	SHEET 1/1	

See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):


CREE LED

LED XHP35 HD
 FWHM / FWTM 51.0 + 18.0° / 84.0 + 50.0°
 Efficiency 77 %
 Peak intensity 2.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




CREE LED

LED XHP35 HI
 FWHM / FWTM 53.0 + 14.0° / 80.0 + 40.0°
 Efficiency 79 %
 Peak intensity 3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




CREE LED

LED XP-G2
 FWHM / FWTM 52.0 + 12.0° / 78.0 + 33.0°
 Efficiency 91 %
 Peak intensity 3.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



CREE LED



LED XP-G3
 FWHM / FWTM 51.0 + 14.0° / 79.0 + 39.0°
 Efficiency 90 %
 Peak intensity 2.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





OPTICAL RESULTS (MEASURED):





LED XP-L HD
 FWHM / FWTM 52.0 + 16.0° / 79.0 + 41.0°
 Efficiency 81 %
 Peak intensity 2.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED LUXEON Rebel ES
 FWHM / FWTM 53.0 + 12.0° / 76.0 + 33.0°
 Efficiency 82 %
 Peak intensity 3.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED SST-10-B130
 FWHM / FWTM 54.0 + 9.5° / 77.0 + 28.0°
 Efficiency 90 %
 Peak intensity 3.8 cd/lm
 LEDs/each optic 1
 Light colour Blue
 Required components:




LED NVSW219D
 FWHM / FWTM 51.0 + 13.0° / 78.0 + 40.0°
 Efficiency 91 %
 Peak intensity 2.9 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





OPTICAL RESULTS (MEASURED):





LED NVSW319B
 FWHM / FWTM 51.0 + 15.0° / 80.0 + 38.0°
 Efficiency 91 %
 Peak intensity 2.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED NVSW3x9A
 FWHM / FWTM 51.0 + 15.0° / 80.0 + 39.0°
 Efficiency 89 %
 Peak intensity 2.5 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:








LED NVSW519A
 FWHM / FWTM 50.0 + 18.0° / 81.0 + 44.0°
 Efficiency 87 %
 Peak intensity 2.1 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED NWSx229A
 FWHM / FWTM 50.0 + 18.0° / 80.0 + 44.0°
 Efficiency 76 %
 Peak intensity 2.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:




OPTICAL RESULTS (MEASURED):

<p> SEOU SEMICONDUCTOR</p> <p>LED Z5M3</p> <p>FWHM / FWTM 52.0 + 13.0° / 79.0 + 39.0°</p> <p>Efficiency 92 %</p> <p>Peak intensity 2.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p> SEOU SEMICONDUCTOR</p> <p>LED Z8Y22P</p> <p>FWHM / FWTM 52.0 + 14.0° / 79.0 + 39.0°</p> <p>Efficiency 90 %</p> <p>Peak intensity 2.5 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		

OPTICAL RESULTS (SIMULATED):




LED XP-G2 HE
 FWHM / FWTM 50.0 + 14.0° / 78.0 + 35.0°
 Efficiency 88 %
 Peak intensity 3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED LUXEON A
 FWHM / FWTM 51.0 + 12.0° / 76.0 + 30.0°
 Efficiency 84 %
 Peak intensity 3.4 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:







LED LUXEON HL2Z
 FWHM / FWTM 54.0 + 10.0° / 76.0 + 28.0°
 Efficiency 89 %
 Peak intensity 3.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



LED LUXEON R
 FWHM / FWTM 53.0 + 12.0°
 Efficiency %
 LEDs/each optic 1
 Light colour White
 Required components:


OPTICAL RESULTS (SIMULATED):

<p>LUMILEDS</p> <p>LED LUXEON SunPlus 20 Line (120 deg)</p> <p>FWHM / FWTM 52.0 + 9.0° / 76.0 + 22.0°</p> <p>Efficiency 91 %</p> <p>Peak intensity 4.6 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p>LUMILEDS</p> <p>LED LUXEON SunPlus 20 Line (150 deg)</p> <p>FWHM / FWTM 52.0 + 10.0° / 76.0 + 20.0°</p> <p>Efficiency 87 %</p> <p>Peak intensity 4.3 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p>NICHIA</p> <p>LED NCSxE17A</p> <p>FWHM / FWTM 54.0 + 24.0° / 180.0 + 54.0°</p> <p>Efficiency 81 %</p> <p>Peak intensity 1.5 cd/lm</p> <p>LEDs/each optic 4</p> <p>Light colour White</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED OSLOM Black</p> <p>FWHM / FWTM 53.0 + 9.0° / 54.0 + 23.0°</p> <p>Efficiency 88 %</p> <p>Peak intensity 4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED	OSLON Black Flat
FWHM / FWTM	54.0 + 8.0° / 74.0 + 18.0°
Efficiency	89 %
Peak intensity	4.8 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)