

FRONT 4-V-7,62-10 6PA BD:1-10 - 1706780

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB terminal block, Nominal current: 32 A, Nom. voltage: 630 V, Number of positions: 10, Connection method: Front screw connection, Mounting: Wave soldering, Conductor/PCB connection direction: 90 °



Key Commercial Data

Packing unit	1 pc
Custom tariff number	85369010
Country of origin	Bulgaria

Classifications

eCl@ss

eCl@ss 4.0	27141109
eCl@ss 4.1	27141109
eCl@ss 5.0	27141190
eCl@ss 5.1	27141190
eCl@ss 6.0	27261101
eCl@ss 7.0	27440401
eCl@ss 8.0	27440401
eCl@ss 9.0	27440401

ETIM

ETIM 4.0	EC002643
ETIM 5.0	EC002643

UNSPSC

UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432

FRONT 4-V-7,62-10 6PA BD:1-10 - 1706780

Approvals

Approvals


Approvals


CSA / UL Recognized / cUL Recognized / EAC / EAC / cULus Recognized


Ex Approvals

Approvals submitted

Approval details

CSA 		B	D
	mm ² /AWG/kcmil	22-10	22-10
	Nominal current I _N	30 A	10 A
	Nominal voltage U _N	300 V	300 V

UL Recognized 		B	D
	mm ² /AWG/kcmil	24-10	24-10
	Nominal current I _N	30 A	10 A
	Nominal voltage U _N	300 V	300 V

cUL Recognized 		B	D
	mm ² /AWG/kcmil	24-10	24-10
	Nominal current I _N	30 A	10 A
	Nominal voltage U _N	300 V	300 V

EAC

FRONT 4-V-7,62-10 6PA BD:1-10 - 1706780

Approvals

EAC

cULus Recognized 