

Tracking camera, lens parameters	
<b>Image sensor</b>	1/2.8inch high quality CMOS sensor
<b>Effective pixels</b>	2,070,000 16: 9
<b>Video signal</b>	1080P60/50/30/25/59.94/29.971080I60/50/59.94720P60/50/30/25 /59.94/29.97
<b>Lens optics zoom</b>	20X optical zoom f=4.7~94mm
<b>Visual angle</b>	2.9° (narrow angle) ~55.4° (wide angle)
<b>Aperture coefficient</b>	F1.6 ~ F3.5
<b>Digital zoom</b>	X10
<b>Minimum illumination</b>	0.5Lux(F1.8, AGC ON)
<b>Digital noise reduction</b>	2D & 3D digital noise reduction
<b>White balance</b>	Manual/auto/one-key white balance /3000K/ 4000K/5000K/6500K
<b>Focus</b>	Auto/manual
<b>Aperture</b>	Auto/manual
<b>Electronic shutter</b>	Auto/manual
<b>Backlight compensation</b>	On/off
<b>Wide dynamic</b>	Off/dynamic grade adjustment
<b>Video regulation</b>	Brightness, hue, saturation, contrast ratio, sharpness, Gamma
<b>Signal to noise ratio</b>	>55dB

Panoramic lens	
<b>Image sensor</b>	1/2.8inch high quality CMOS sensor
<b>Effective pixels</b>	2,100,000
<b>Lens</b>	Manual focus
<b>Output port</b>	Network port, HDMI, USB
<b>Field angle (D/H/V)</b>	112°/82°/57.6°

Input/output port and support protocol	
<b>Video port</b>	HDMI
<b>Network port</b>	100M internet access (10/100BASE-TX) 5GWiFi(optional), support network VISCA control protocol
<b>Network protocol</b>	RTSP, RTMP, ONVIF, GB/T28181

<b>Compression image code stream</b>	Dual stream output
<b>Video compression format</b>	H.265, H.264
<b>Control signal port</b>	RS-232/485
<b>Control protocol</b>	VISCA/Pelco-D/Pelco-P; Baud rate: 115,200/9,600/4,800/2,400bps
<b>Audio input port</b>	Dual track 3.5mm linear input
<b>Audio compression format</b>	AAC, MP3, PCM
<b>Power port</b>	HEC3800 power socket (DC12V)

<b>Holder parameters</b>	
<b>Horizontal rotation</b>	-170°~+170°
<b>Vertical rotation</b>	-30°~+90°
<b>Horizontal control speed</b>	0.1 ~100°/s
<b>Vertical control speed</b>	0.1~45°/s
<b>Preset speed</b>	Horizontal: 100°/s, vertical:45°/s
<b>Preset quantity</b>	User can set 255 presets at most (10 pcs of mobile control)

<b>Other parameters</b>	
<b>Power adapter</b>	Input AC110V-AC220V output DC12V/2.5A
<b>Input voltage</b>	DC12V±10%
<b>Input current</b>	1.5A (maximum)
<b>Power consumption</b>	18W (maximum)
<b>Storage temperature</b>	-10°C~+60°C
<b>Storage humidity</b>	20%~95%
<b>Operating temperature</b>	-10°C~+50°C
<b>Operating humidity</b>	20%~80%
<b>Dimension (WxHxD)</b>	254mm X 144mm X 174mm
<b>Weight (approx.)</b>	1.50kg
<b>Operating environment</b>	Indoor
<b>Remote maintenance (network port)</b>	Remote upgrade, restart and reset