

USB Sync/Charge Cable with Apple 30-Pin Dock Connector, Black, 10 in. (.24 m)

MODEL NUMBER: **M110-10N-BK**



Charge and sync your Apple 30-pin iPhone, iPad or iPod using the USB port on your computer.

Description

The M110-10N-BK USB Sync/Charge Cable connects your iPhone, iPad or iPod with the USB port on a computer, so you can charge your Apple device and transfer data. Compatible with all computers, this 10-inch cable is MFi-certified for use with iPhone, iPad and iPod devices. It's compatible with iPhone (4s, 4, 3Gs, 3G and iPhone), iPad (3rd generation), iPad 2, iPad, iPod Touch (1st through 4th generation), iPod classic and iPod nano (1st through 6th generation). The M110-10N-BK is ideally sized to charge devices in Tripp Lite's CS16USB, CS32USB and CS48USB Tablet Charging Stations.

Features

Syncs and Charges Your Apple 30-Pin Electronic Devices

- MFi-certified for use with iPhone, iPad and iPod devices
- Compatible with iPhone (4s, 4, 3Gs, 3G and iPhone), iPad (3rd generation), iPad 2, iPad, iPod Touch (1st through 4th generation), iPod classic and iPod nano (1st through 6th generation)

Compact and Convenient to Use

- Connects your 30-pin iPhone, iPad or iPod device and the USB port on your computer or wall charger
- Works with any computer
- Fits in your laptop bag for use away from home or office
- Conveniently sized for Tripp Lite's CS16USB, CS32USB and CS48USB Tablet Charging Stations

Specifications

OVERVIEW

UPC Code

037332190048

Highlights

- Features an Apple-compatible 30-pin plug and a USB-A plug
- Works with any computer
- MFi-certified for use with iPhone, iPad and iPod devices
- Compatible with all Apple devices with 30-pin connectors
- Perfectly sized for Tripp Lite's Tablet Charging Stations

System Requirements

- USB-equipped computer or charger
- iPhone (4s, 4, 3Gs, 3G and iPhone), iPad (3rd generation), iPad 2, iPad, iPod Touch (1st through 4th generation), iPod classic and iPod nano (1st through 6th generation)

Package Includes

- M110-10N-BK USB Sync/Charge Cable with Apple 30-Pin Dock Connector



Technology	Apple® 30-Pin Dock; USB
PHYSICAL	
Color	Black
Cable Jacket Rating	VW-1
Cable Outer Diameter (OD)	2.8mm
Cable Length (ft.)	0.8
Cable Length (m)	0.24
Cable Length (in.)	10
Material of Construction	PVC
Shipping Dimensions (hwd / cm)	11.68 x 6.10 x 2.29
Shipping Dimensions (hwd / in.)	4.60 x 2.40 x 0.90
Shipping Weight (kg)	0.03
Shipping Weight (lbs.)	0.07
Unit Packaging Type	Box
ENVIRONMENTAL	
Operating Temperature Range	-4 to 140 F (-20 to 60 C)
Storage Temperature Range	-4 to 176 F (-20 to 80 C)
Relative Humidity	0% to 90% RH, Non-Condensing
CONNECTIONS	
Side A - Connector 1	USB A (MALE)
Side B - Connector 1	30 PIN APPLE (MALE)
Connector Plating	Nickel
Contact Plating	Gold
FEATURES & SPECIFICATIONS	
USB Specification	USB 2.0 (up to 480 Mbps)
STANDARDS & COMPLIANCE	
Certifications	Tested to MFI, CA65, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>