

## RF TERMINATION Type 6525.41.AA

### Description

Standard Termination, Medium Power



### Product Configuration

Connector	7/16 plug (male)
Interface standards	IEC 60169-4_CECC 22190_DIN 47223_VG 95250

### Technical Data

#### Electrical Data

Nominal Impedance	50 $\Omega$
Frequency range	0 to 5 GHz
Frequency sub range	DC to 2 GHz      2 to 5 GHz
VSWR max.	1.1      1.2
Power rating	25 Watt average power up to 25 °C ambient temperature, linearly derated to 0 Watt at 150 °C ambient temperature. 1500 Watt peak power , 5 $\mu$ s pulse, 0.05 % duty cycle

#### Mechanical Data

Weight	0.204 kg
--------	----------

#### Environmental Data

Operating temperature 2011/65/EU (RoHS - including 2015/863 and 2017/2102)	-40 °C to 150 °C compliant
--	-------------------------------

#### Material Data

Piece Part	Material	Surface Plating
Centre contact	Brass	Silver Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Aluminium	Anodized
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00005462
-----------------	--------------

### Ordering Information

Single Packaging Packaging	6525.41.AA
-------------------------------	------------

### Additional Information

Important note	WARNING Beryllia Ceramic Inside! DO NOT sand, scrap or tamper with. Dispose in accordance with all relevant regulations.
----------------	--