

## Specification Sheet

Part Number: 155-03800



Connector Clip w/Fir Tree, 0.7 - 6.0 mm Panel Thickness, 6.5 - 7.0 mm Hole Dia, PA66HIRHS, Black, 500/pkg

**Article Number**

155-03800

**Type**

FT6LG-AMP

**Color**

Black (BK)

**Features & Benefits**

- Head design contains clamping rails to provide full circumferential compression around bundles.
- Bent tail allows for quick insertion into head.

**Quantity Per**

bag

**Product Description**

Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

|                                                |                                                                                                           |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>Short Description</b>                       | Connector Clip w/Fir Tree, 0.7 - 6.0 mm Panel Thickness, 6.5 - 7.0 mm Hole Dia, PA66HIRHS, Black, 500/pkg |
| <b>Global Part Name</b>                        | FT6LG-AMP-PA66HIRHS-BK                                                                                    |
| <b>Fixation Method</b>                         | Fir Tree                                                                                                  |
| <b>Panel Thickness Min(Imperial)</b>           | 0.028                                                                                                     |
| <b>Panel Thickness Max(Imperial)</b>           | 0.24                                                                                                      |
| <b>Panel Thickness Min (Metric)</b>            | 0.7                                                                                                       |
| <b>Panel Thickness Max (Metric)</b>            | 6.0                                                                                                       |
| <b>Mounting Hole Diameter D (Imperial)</b>     | 0.26 - 0.28                                                                                               |
| <b>Mounting Hole Diameter D (Metric)</b>       | 6.5 - 7.0 mm                                                                                              |
| <b>Mounting Hole Diameter D Min (Imperial)</b> | 0.26                                                                                                      |
| <b>Mounting Hole Diameter D Max (Imperial)</b> | 0.28                                                                                                      |
| <b>Mounting Hole Diameter D Max (Metric)</b>   | 7.0                                                                                                       |
| <b>Disc Diameter(Metric)</b>                   | 16.0                                                                                                      |
| <b>Disc Diameter (Imperial)</b>                | 0.63                                                                                                      |
| <b>Material</b>                                | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)                                          |

**Material Shortcut**

PA66HIRHS

**Flammability**

UL 94 HB

**Operating Temperature (Metric)**

-40°F to +221°F (-40°C to +105°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

500

**Package Quantity (Metric)**

500

**Customs Number**

3926909988

**Content Unit(BMEcat)**

pcs.

**Weight (Metric)**

0.88