

Specification Sheet

Part Number: 170-03015



Cuts with scissors without fraying ends enables field installations without need for hot knife.

Expands to 150% of easy installation and reduced assembly time requirements.

Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.

Braided Sleeving, Expandable, Fray Resistant, 1.25" Dia, PET, Black, 50 ft/reel

Article Number 170-03015

Type BSPSC1140

Color Black (BK)

Quantity Per reel

Product Description A versatile and economical general purpose sleeving that resists fraying

when cut with ordinary scissors. For use in automotive, industrial and computer applications where the wires, cables and hoses being covered endure frequent handling. It is suited for situations where

access to a hot knife is either impractical or impossible.

Short Description Braided Sleeving, Expandable, Fray Resistant, 1.25" Dia, PET, Black,

50 ft/reel

Global F	Part Name
----------	-----------

BSPSC1140-PET-BK

Length L (Imperial)	50.0
Length L (Metric)	15.2
Bundle Diameter Min (Imperial)	1.0
Bundle Diameter Min (Metric)	25.4
Bundle Diameter Max (Imperial)	1.5
Bundle Diameter Max (Metric)	38.1
Diameter D (Imperial)	1.25
Diameter D (Metric)	31.8
Nominal Diameter (Imperial)	1.25
Nominal Diameter (Metric)	31.8
Material	Polyester (PET)
	. 3., 33.01 (1 2 1)
Material Shortcut	PET

Halogen Free

Flammability

Yes

UL 94 V-0

UV Resistant (Yes/No)

No

Operating Temperature

-94°F to +257°F (-70°C to +125°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant

Yes

UL Recognized (US)

Yes

Package Quantity (Imperial)

50

Package Quantity (Metric)

15.24

About HellermannTyton

Customs Number

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

5808100000

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions