

## Single relay - REL-MR- 24AC/21-21/MS - 2987956

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in miniature relay, with power contact, 2 PDTs, test button, mechanical switch position indicator, status LED, input voltage 24 V AC

### Your advantages

- ✓ With detectable manual operation
- ✓ Switching current of up to 16 A
- ✓ DC types with integrated freewheeling diode
- ✓ Integrated status LED
- ✓ Mechanical switch position indicator



COMPLIES WITH

### Key Commercial Data

|                        |                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit           | 10 pc                                                                                                   |
| Minimum order quantity | 10 pc                                                                                                   |
| GTIN                   | <br>4 046356 480666 |
| GTIN                   | 4046356480666                                                                                           |

### Technical data

#### Dimensions

|        |         |
|--------|---------|
| Width  | 12.7 mm |
| Height | 29 mm   |
| Depth  | 25 mm   |

#### Ambient conditions

|                                         |                  |
|-----------------------------------------|------------------|
| Ambient temperature (operation)         | -40 °C ... 70 °C |
| Ambient temperature (storage/transport) | -40 °C ... 85 °C |

#### Coil side

|                             |          |
|-----------------------------|----------|
| Nominal input voltage $U_N$ | 24 V AC  |
| Mains frequency             | 50/60 Hz |

# Single relay - REL-MR- 24AC/21-21/MS - 2987956

## Technical data

### Coil side

|                                         |                                              |
|-----------------------------------------|----------------------------------------------|
| Typical input current at $U_N$          | 32 mA                                        |
| Typical response time                   | 3 ms ... 12 ms (depending on phase relation) |
| Typical release time range              | 2 ms ... 8 ms (depending on phase relation)  |
| Power dissipation for nominal condition | 0.77 W                                       |

### Contact side

|                                       |                                |
|---------------------------------------|--------------------------------|
| Contact type                          | 2 PDT                          |
| Type of switch contact                | Single contact                 |
| Contact material                      | AgNi                           |
| Maximum switching voltage             | 250 V AC/DC                    |
| Minimum switching voltage             | 12 V (at 10 mA)                |
| Min. switching current                | 10 mA (at 12 V)                |
| Maximum inrush current                | 16 A (20 ms)                   |
| Limiting continuous current           | 8 A                            |
| Interrupting rating (ohmic load) max. | 2000 VA (for 250 V AC)         |
| Switching capacity                    | 1 A (at 24 V, DC13)            |
|                                       | 1.5 A (at 24 V, AC15)          |
|                                       | 1.5 A (at 120 V, AC15)         |
|                                       | 1.5 A (at 240 V, AC15)         |
| Motor load according to UL 508        | 1/4 HP, 120 V AC (N/O contact) |
|                                       | 1/2 HP, 240 V AC (N/O contact) |
|                                       | 1/4 HP, 120 V AC (N/C contact) |
|                                       | 1/3 HP, 240 V AC (N/C contact) |

### General

|                                          |                           |
|------------------------------------------|---------------------------|
| Test voltage relay winding/relay contact | 5 kV AC (50 Hz, 1 min.)   |
| Test voltage relay contact/relay contact | 2.5 kV AC (50 Hz, 1 min.) |
| Mechanical service life                  | 5x 10 <sup>6</sup> cycles |
| Service life, electrical                 | see diagram               |

### Connection data

|                   |                   |
|-------------------|-------------------|
| Connection method | Solder connection |
|-------------------|-------------------|

### Standards and Regulations

|                                  |              |
|----------------------------------|--------------|
| Connection in acc. with standard | CUL          |
| Standards/regulations            | EN 61810-1   |
|                                  | VDE 0435-201 |
|                                  | EN 50178     |


### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Single relay - REL-MR- 24AC/21-21/MS - 2987956

### Drawings


Diagram



Operating voltage range

## Single relay - REL-MR- 24AC/21-21/MS - 2987956


Diagram



Interrupting rating


## Single relay - REL-MR- 24AC/21-21/MS - 2987956

Diagram



Electrical service life


Diagram



Service life reduction factor with various cos phi

## Single relay - REL-MR- 24AC/21-21/MS - 2987956

Dimensional drawing



### Approvals

#### Approvals

#### Approvals

UL Recognized / cUL Recognized / VDE Zeichengenehmigung / EAC / EAC / cULus Recognized

#### Ex Approvals

### Approval details

UL Recognized



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

FILE E 195083

cUL Recognized



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

FILE E 195083

VDE Zeichengenehmigung



<http://www2.vde.com/de/Institut/Online-Service/VDE-gepruefteProdukte/Seiten/Online-Suche.aspx>

40027210

## Single relay - REL-MR- 24AC/21-21/MS - 2987956

### Approvals

|     |                                                                                   |                 |
|-----|-----------------------------------------------------------------------------------|-----------------|
| EAC |  | TR_TS_D_00573_c |
|-----|-----------------------------------------------------------------------------------|-----------------|

|     |                                                                                   |                 |
|-----|-----------------------------------------------------------------------------------|-----------------|
| EAC |  | TR_TS_S_00010_c |
|-----|-----------------------------------------------------------------------------------|-----------------|

|                  |                                                                                   |  |
|------------------|-----------------------------------------------------------------------------------|--|
| cULus Recognized |  |  |
|------------------|-----------------------------------------------------------------------------------|--|

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>