

## Specification Sheet

Part Number: T120MR9K2



1-Piece Cable Tie/Screw Mount, 15.6" Long, #1/4 Screw, 4.02" Max Bundle Dia, 120lb, PA66, Natural, 50/pkg

<b>Article Number</b>	113-12029
<b>Type</b>	T120MR
<b>Color</b>	Natural (NA)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Screw mount style creates low insertion and high extraction force.</li><li>•Choose from several tensile strengths and lengths to accommodate a range of applications.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	One-piece Screw Mount Cable Ties fasten with a screw or bolt to provide secure routing of cable bundles. Multiple configurations are available to cover a range of bundle sizes and tensile strengths.
<b>Short Description</b>	1-Piece Cable Tie/Screw Mount, 15.6" Long, #1/4 Screw, 4.02" Max Bundle Dia, 120lb, PA66, Natural, 50/pkg

Global Part Name

T120MR-PA66-NA

Minimum Tensile Strength (Imperial)

120.0

Minimum Tensile Strength (Metric)

535

Length L (Imperial)

15.6

Length L (Metric)

395.0

Fixation Method

Fixing hole

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Inside Serrated

Width W (Imperial)

0.3

Width W (Metric)

7.6

Bundle Diameter Min (Imperial)

0.2

Bundle Diameter Min (Metric)

5.0

Bundle Diameter Max (Imperial)

4.0

Bundle Diameter Max (Metric)

102.0

Thickness T (Imperial)

0.07

<b>Thickness T (Metric)</b>	1.8
<b>Cable Tie Head Length (Imperial)</b>	1.12
<b>Cable Tie Head Width (Imperial)</b>	0.51
<b>Height H (Imperial)</b>	.31
<b>Height H (Metric)</b>	7.90
<b>Mounting Hole Diameter D (Imperial)</b>	0.26
<b>Mounting Hole Diameter D (Metric)</b>	6.5 mm
<b>Mounting Hole Diameter D Max (Metric)</b>	6.5
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL   ANSI/UL 746B UL   ANSI/UL 62275 UL   ANSI/UL 1565
<b>UL Recognized (US)</b>	Yes

<b>UL Listed (US and Canada)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>UL Listed (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	50
<b>Package Quantity (Metric)</b>	50
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	5.8