

Coaxial Cable Connector 21_N-50-3-11/133_N

Description

Straight cable jack

Interface standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 18 GHz |

Mechanical Data

| | |
|----------------|-----------|
| Centre contact | soldered |
| Outer contact | soldered |
| Weight | 0.0378 kg |

Environmental Data

| | |
|--|------------------|
| Operating temperature | -65 °C to 165 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|-----------------------------------|
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

Related Documents

| | |
|----------------------|----------------|
| Catalogue drawing | DOU-00007451 |
| Assembly instruction | DOC-0000350737 |

Ordering Information

| | |
|----------------|---------------------|
| Single package | 21_N-50-3-11/133_NE |
|----------------|---------------------|

Additional Information

| | |
|-----------------|---------------|
| Suitable cables | EZ_141_TP_M17 |
|-----------------|---------------|