XE2NP2138

Limit switch contact block, Limit switches XC Standard, 1 co, 2 NO sl with gold flashed connector



Main

Range of Product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or Component Type	Limit switch contact block
Device short name	XE2N
Associated body	ZCP28 ZCD28 ZCKJ8 ZCKL8 ZCKS8 ZCKS8 ZCKJ8D ZCKM8
Number of poles	2
Contacts type and composition	2 NO
Contact operation	Slow-break, simultaneous

Complementary

Product Compatibility	XCKP	
·	XCKL	
	XCKJ	
	XCKD	
	XCKM	
	XCKS	
Electrical connection	Screw-clamp terminals 1 x 0.52 x 2.5 mm ²	
Contacts insulation form	Zb	
Contacts material	Gold flashed contacts	
Positive opening	Without	
Minimum actuation speed	6 m/min	
Contact code designation	A300, AC-15 (Ue = 240 V), Ie = 3 A 10 A EN/IEC 60947-5-1 appendix A	
ŭ	Q300, DC-13 (Ue = 250 V), le = 0.27 A EN/IEC 60947-5-1 appendix A	
Maximum resistance across terminals	25 mOhm IEC 60255-7 category 3	
[Ui] rated insulation voltage	300 VUL 508	
	500 V 3)IEC 60947-1	
	300 VCSA C22.2 No 14	
[Uimp] rated impulse withstand voltage	6 KV IEC 60664	
	6 kV IEC 60947-1	
Short-circuit protection	cuit protection 10 A cartridge fuse gG	
Electrical durability	5000000 Cycles, DC-13 120 V, 7 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C	
	5000000 Cycles, DC-13 24 V, 13 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C	
	5000000 cycles, DC-13 48 V, 9 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C	

Ordering and shipping details

Category	22449-LIMIT SWITCHES, ACCESSORIES	
Discount Schedule	Т	
GTIN	3389110196214	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.74 oz (21.0 g)	
Returnability	No	
Country of origin	FR	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	4.33 in (11 cm)	
Package 1 width	0.98 in (2.5 cm)	
Package 1 Length	2.95 in (7.5 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
vvarianty	10 months